

The Additional P.C.C.F. (Central) Eastern Regional Office Ministry of Environment, Forests & Climate Change Government of India A/3, Chandrashekharpur, Bhubaneswar - 751 023, Odisha

KPO/Env/C-05/ 11 /2018 25.05.2018

Dear Sir,

Sub.: Six monthly Compliance Report for Oct-17 to Mar-18 for Environmental Clearances in respect of 6.0 MTPA Integrated Steel Plant of M/s. Tata Steel at Kalinganagar Industrial Complex, Duburi, Dist. Jajpur, Odisha.

Ref.: EC Granted by MoEF vide Letter No. J-11011/7/2006-IA-II(I) dated 7.11.2006. : Amendments in EC granted by MoEF vide Letters No. J-11011/7/2006-IA-II (I) dated 10.12.2012 and 13.05.2015

Kindly find enclosed Six Monthly Compliance Report for the period from Oct 2017 to Mar 2018 for the conditions stipulated in Environmental Clearance including amendments granted in EC to 6.0 MTPA Integrated Steel Plant of Tata Steel Limited at Duburi, Dist. Jajpur, Odisha for your kind considerations.

Copy of the compliance report is also being sent in soft format through e-mail (roez.bsrmef@nic.in), for your kind perusal.

We trust the information furnished is in line with your requirement.

Thanking you,

Yours faithfully,

Copy to MS, OSPCB, Bhubaneswar / CPCB Kolkata Posposik Negronal 51023

### Six Monthly Environment Compliance Report Oct' 2017 to Mar' 2018

For

Integrated Steel Plant Project of Tata Steel

At

Duburi, Dist. Jajpur, Odisha



Environment Department **Tata Steel Limited**Kalinganagar Industrial Complex

Duburi- 755026

Dist Jajpur, Odisha

#### Specific Conditions as per EC dated 7.11.2006 Status as on 31.03.2018 A i) The gaseous emissions from various process units • All the process units such as Coke Plant, Sinter shall conform to the load/mass based standards Plant, Blast Furnace, SMS, and Mill have been notified by this Ministry on 19th May, 1993 and designed conforming to the load/mass standards standards prescribed from time to time. The state notified by the Ministry to have the gaseous Boards may specify more stringent standards for emissions under control and below the prescribed the relevant parameters keeping in view the nature limits. of the industry and its size and location. At no time, • Online continuous stack monitoring systems have the emission level shall go beyond the prescribed been installed at stacks of Coke Plant Battery standards. On-line continuous monitoring system No.1 and 2, Sinter Plant, BF, SMS, LCP and shall be installed in stacks to monitor SPM and HSM to monitor SPM. interlocking facilities shall be provided so that • The units are in operation and emission levels process can be automatically stopped in case were found within prescribed norms. emission level exceeds the limit. Nox burners shall • Low NOx burners are installed at CPP (8 Nos for be installed to control NOx levels. VOCs from the each boilers in all three boilers) and in HSM coke oven shall be monitored and controlled as per reheating furnace (84 Nos) CPCB guidelines. The new standards prescribed • VOC from coke plant is controlled by On-main by the CPCB for coke oven plants shall be strictly charging by HPLA, Hydraulic doors, Door followed. sealing, Door frame cleaner, etc. as per CPCB guidelines and the systems for both the Battery No. 1 as well as Battery -2 are in operations. • New standards prescribed by CPCB (31.03.2012) for coke ovens are being followed. ii. In-plant control measures for checking fugitive • In plant control measures (like Dust extraction emissions from all the vulnerable sources like systems- DES, Dust Suppression System- DSS coke oven area, Sinter Plant, BF case house, BF and Dry Fog dust suppression systems- DFDSS) stack house, and BOF shop etc. shall be provided. are controlling fugitive emissions from the Further, specific measures like water sprinkling vulnerable sources like coke oven area, Sinter and dry fogging (DF) shall be carried out at the Plant, BF case house, BF stack house, and BOF stock piles of raw materials, stacker reclaimer, shop etc. conveyor transfer points and vibrating screens etc. • Further specific measures like water sprinkling Dust extraction system and bag filter shall be arrangement at stock piles of raw materials and provided for room air cleaning such as sinter plant stacker reclaimer. DE, DSS and DFDS are stock house, BF stock house and BF cast house, provided at conveyor transfer points and BOF shop and Ferro-alloys handling area in steel vibrating screens to control fugitive dusts from melting shop etc. Fume extraction system in steel these sources. refining units shall also be provided. Centralized • Dust extraction system followed by De-dusting de-dusting system i.e. collection of fugitive ESP has been provided at Sinter Plant. At Cast emissions through suction hood and subsequent house and Stock house of Blast Furnace, separate treatment through bag filter or any other device dust extraction systems followed by ESPs have and finally emitted through a stack of been provided. In SMS, secondary de-dusting appropriately designed and height conforming to unit (Cyclone separator followed by ESP) has the standards for induction furnaces in the been provided. Fume extraction system in steel industry shall be provided. Fugitive emissions refining units has been provided. All the stacks shall be controlled, regularly monitored and have been designed and installed to meet the records maintained. requirement of stack heights as per guidelines, for proper dispersion and dilution of pollutants • In addition to above, following control measures are taken to control of fugitive emissions from other sources are:o Water sprinkling on roads is being done through truck mounted water tankers to

A	Specific Conditions as per EC dated 7.11.2006	Status as on 31.03.2018
		suppress road dust due to vehicular movement.
		<ul> <li>To suppress fine dusts, specially designed vehicle for mist type sprinkling of water (through movable High Pressure Mechanized Water jet) has been deployed.</li> <li>Mechanized road sweeping Machines have been deployed for regular road sweeping.</li> <li>Speed limits are enforced for movement of vehicles at the site as per the factory limits</li> <li>Roads (about 22 kms) within the plant site are metaled/ concreted.</li> </ul>
iii.	ESP shall be provided to sinter plant and blast furnace. New standards prescribed by the CPCB for coke oven shall be strictly followed. The Company shall install Waste Heat Recovery Boilers (WHRB) to recover the waste heat and generate power from the steam produces by the WHRB. The particulate emissions from the WHRB shall be controlled by installation of ESP as per CPCB specification and particulate emissions shall not exceed 50mg/Nm³. Further, the company shall install bag filter, After Burner Chamber (ABC), suction hood, dust extraction device and fume extraction system to control gaseous emissions from the WHRB.	<ul> <li>ESPs with higher efficiency have been provided to Sinter plant, Blast Furnace and SMS.</li> <li>Coke oven plant is designed to comply with new standards prescribed by CPCB for Coke Oven.</li> <li>Waste Heat Recovery Boilers (WHRB) have been installed to recover waste heat which in turn shall be used for in-house power generation from the steam produces by WHRB.</li> <li>Pollution Control Systems have been designed as per CPCB guidelines to control PM emissions below 50 mg/Nm3.</li> </ul>
iv.	Total requirement of the water from Brahmani /Kharasua river shall not exceed 26.5 MGD. No ground water shall be drawn and used for the plant. The effluent quantity into the industrial drain leading to the Gonda Nalla shall not exceed 92m³/hr and shall conform to the prescribed standards. Ammonia, phenol and cyanide in the effluent should be treated separately and discharged only after meeting the norms prescribed by the OSPCB/CPCB/Ministry under E(P) Act. Cyanide shall meet the standard of 0.2 ppm. TDS in the effluent discharged shall not be more than 2,100 mg/I. The domestic wastewater after treatment in STP shall be used for green belt development.	<ul> <li>Make up water requirement for the plant is &lt; 26.5 MGD. Present water consumption is around 8 MGD.</li> <li>Total effluent discharge envisaged is &lt; 92 m³/hr and it meets the standards prescribed by MoEF/CPCB/OSPCB before discharge into Ganda Nalla.</li> <li>Ammonia, Phenol, Cyanide from Coke Oven plant is treated separately in BOD plant meant for the treatment of effluent generated from Coke Plant. The BOD plant is in operation.</li> <li>For Domestic wastewater there is a STP.</li> <li>Treated water is utilized for plantation.</li> <li>No groundwater is used for plant operations.</li> </ul>
v.	Ground water monitoring around the solid waste disposal site/secured landfill (SLF) shall be carried out regularly and report submitted to the Ministry's Regional Office at Bhubaneswar, CPCB and OPCB.	<ul> <li>Ground water level is monitored and variations are negligible.</li> <li>Ground water quality is within the permissible limit.</li> </ul>
vi.	BF slag shall be sold to the cement manufacturers after granulation. Non-granulated BF slag shall be used in road making. BOF slag shall not be dumped anywhere except used for making cement and road etc. proposed in EIA/EMP. Ammonia and tar shall be recovered and remaining solid waste shall be burnt. Gas cleaning plant sludge and mill scales shall be reused in the sinter plant. Char generated	<ul> <li>BF slag is sold to cement manufacturers after online slag granulation process (RASA). Majority of BF slag is transported by rail.</li> <li>Non-granulated BF slag is used for road making; non-granulated BOF slag is also used for road making.</li> <li>In COBPP, Tar and Sulphur is recovered and same is sold as by-product.</li> </ul>

A	Specific Conditions as per EC dated 7.11.2006	Status as on 31.03.2018
	shall be used in FBC boiler. The kiln accretions	• Gas cleaning plant is in operation in BF & SMS.
	shall be utilized for filling low lying areas. The	Mill scales from mills are being utilized in sinter
	entire quantity of fly ash generated during the	plant.
	process shall be utilized for making brick. ESP fly	• No fly ash & bottom ash is generated in process.
	ash shall be made available to the cement plants	
	and brick making plants whereas bottom ash shall	
	be disposed off in a suitably designed landfill as	
	per CPCB guidelines to prevent leaching to the	
vii.	sub-soil and underground aquifer.  The company shall develop surface water	• Cumfo as mun off during the managen is collected
VII.	harvesting structures to harvest the rain water for	• Surface run-off during the monsoon is collected and stored in the reservoirs constructed under
	utilization in the lean season besides recharging the	rain water harvesting schemes.
	ground water table.	• Storm water pond with necessary pumping
	grown water there.	arrangement to recover storm water in raw water
		system has been made.
viii.	Green belt shall be developed in at least 33% area	Green Belt cover is being continuously
	within and around the plant premises as per the	developed within and around the project site, as
	CPCB guidelines in consultation with DFO.	well as outside the plant premises (rehabilitation
		colonies).
		<b>Details of tree saplings planted:</b>
		2009-10: 792 nos 2013-14: 29888 nos.
		2010-11: 1130 nos 2014-15: 35437 nos.
		2011-12: 4800 nos. 2015-16: 78730 nos.
		2012-13: 12622 nos. 2016-17: 77335 nos.
		2017-18: 100701 nos.
		Avenue plantation was done at Jajpur town,
ix.	Occupational Health Surveillance of the grantons	Kalinganagar and Bhubaneswar.
IX.	Occupational Health Surveillance of the workers	• Initial & Periodic medical check-up for workers
	shall be done on a regular basis and records maintained as per the factories Act.	are carried out and records for the same are maintained as per the Factories Act.
	manitamed as per the factories rect.	To strengthen the Occupational Health
		Surveillance, a system has been made, in which,
		employee's Gate Pass is issued only after
		ensuring the initial medical check-up.
х.	Recommendations made in the CREP guidelines	CREP recommendations are being implemented
	issued for the steel plants shall be implemented.	and summarized below:
		1. Coke Ovens: Fugitive emission control
		system is in place. All the batteries are new
		one and having coal stamping, charging cum
		pushing (SCP) machines.
		2. SMS: Secondary fume extraction system has
		been installed.
		3. BF: Pulverized Coal injection facilities have
		been installed in Blast Furnaces, TRT, Tar Free Runners, DE system at Cast House, etc
		are also provided.
		4. Specific water consumption is less than 8 m <sup>3</sup> /t
		of flat product.
		5. Online monitoring facilities have been
		provided.
		6. Waste management systems are implemented.
xi.	Rehabilitation and Resettlement plan shall be	• Families have been rehabilitated within the
	implemented as per the revised R&R policy and in	framework of "Tata Steel Parivaar" concept as
i	collaboration with the State Government in a time	per R & R policy of Odisha Govt. in consultation

A	Specific Conditions as per EC dated 7.11.2006	Status as on 31.03.2018
	bound manner and report submitted to the	with the local administration. A dedicated team
	Ministry, it's Regional Office at Bhubaneshwar	facilitates the resettlement & rehabilitation
	and OPCB.	effectively.
xii.	The environmental clearance for the mining	• The matter is being pursued with State and
	project and forest clearance for the forest land	Central Government.
	involved in the mining project shall be obtained	Coal is being imported.
	from the Ministry prior to operation of the	• Source of iron ore is mainly from the mines of
	integrated Steel Plant. In case, environmental	Tata Steel in Odisha.
	clearance for the mining proposal from State	
	Govt/Govt. of India is not available, Ministry shall	
	be regularly informed about the source of ore and	
	coal.	

В.	General Conditions as per EC dated 7.11.2006	Status as on 31.03.2018
i.	The project authorities must strictly adhere to the stipulations made by the Orissa Pollution Control Board (OPCB) and the State Government	During project execution and subsequent operation phases TSL has strictly adhere to stipulation made by OSPCB and the state Government
ii.	No further expansion or modification in the plant should be carried out without prior approval of the Ministry of Environment and Forests.	<ul> <li>Amendments in the Environmental Clearance were granted by MoEF on 10.10.2012 and on 13.05.2015 vide letters no. J-11011/7/2006-IA.II.(I).</li> <li>Our application regarding expansion from 6 MTPA to 8 MTPA has been submitted on 20.09.2016. ToR for expansion was reviewed by EAC Industry-I on 28.10.2016 and granted in March 2017. EIA Report is under preparation.</li> </ul>
iii.	At least four ambient air quality-monitoring stations should be established in the downward direction as well as where maximum ground level concentration of SPM, SO <sub>2</sub> and NOx are anticipated in consultation with the OPCB. Data on ambient air quality and stack emission should be regularly submitted to this Ministry including its Regional Office at Bhopal and the OPCB/CPCB once in six months.	<ul> <li>Ambient Air quality monitoring Stations are established.</li> <li>Data on Ambient Air Quality and Stack emissions are submitted regularly on monthly basis to OSPCB and Half yearly basis to MoEF&amp;CC.</li> <li>Data of Online Continuous Ambient Air quality monitoring stations as well as Continuous Emission Monitoring Systems of Stacks are also being transferred to the server of OSPCB through Real Time Data Acquisition System (RTDAS).</li> </ul>
iv.	Industrial waste water shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 dated 19 <sup>th</sup> May, 1993 and 31 <sup>st</sup> December, 1993 or as amended from time to time. The treated wastewater shall be utilized for plantation purpose.	<ul> <li>For Treatment of Industrial waste water and its recovery and reuse, individual units like Coke Plant, HSM, SMS and BF etc. have individual Waste Water Treatment units in operation.</li> <li>Excess treated water from individual treatment plant is sent to Central Effluent Treatment Plant (CETP). CETP is in operation with tertiary treatment. The Treated water from CETP is used in process.</li> <li>Treated wastewater will be also used for plantation, dust suppression &amp; other uses.</li> </ul>

В.	General Conditions as per EC dated 7.11.2006	Status as on 31.03.2018						
v.	The overall noise levels in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75 dBA (daytime) and 70 dBA (nighttime).	<ul> <li>Low noise prone rotary equipment and vibration dampening has been one of the design aspects as a control measure for noise pollution.</li> <li>Provision of acoustic hoods, silencers in steam ejectors as well as sound proof enclosures have also been made at various internal sites.</li> </ul>						
vi.	The project proponent shall also comply with all the environmental protection measures and safeguards recommended in the EIA/EMP report. Further, the company must undertake socioeconomic development activities in the surrounding villages like community development programmes, educational programmes, drinking water supply and health care etc.	<ul> <li>Environmental protection measures as proposed in the EIA and EMP report is being implemented.</li> <li>Various socio-economic developmental activities in the area of Health, Women Empowerment, Education, Sports &amp; culture, Infrastructure development etc. are on-going in 28 villages surrounding the project site. Recently, 5 medical mobile units have been added for immediate treatment to the local people.</li> <li>Multi-specialty, 100 bedded hospitals (<i>Medica TS</i>) is now functioning very close to the plant site for facilitating health service to the community.</li> </ul>						
vii.	The project authorities shall utilize Rs.1,525.00 Crores earmarked for the environmental pollution control measures judiciously to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.	Funds earmarked for the environmental pollution control measures are not diverted and is being utilized only for the said purpose.						
viii.	The Regional Office of this Ministry at Bhopal/CPCB/OPCB will monitor the stipulated conditions. A six monthly compliance report and the monitored data along with statistical interpretation shall be submitted to them regularly.	Six monthly compliance reports are being submitted regularly.  Last Report Sent on 01.12.2017.						
X	the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the OPCB/Committee and may also be seen at Website of the Ministry of Environmental and Forests at http:/envfor.nic.in. This shall be advertises within seven days from the date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same shall be forwarded to the Regional office.  Project authorities should inform Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of commencing the land	News paper advertisement details:-  Newspaper Language Date New Indian Express English 13.06.06 Sambad Odia 13.06.06  Complied.						
	development work.							

	Additional Conditions vide letter dated 10.10.2012	Status as on 31.03.2018
i)	The company shall install low NOx burners to mitigate NOx emissions from captive power plant.	There are three nos. of boilers of captive power plant. At each boiler, 8 Nos. of Low NOx burners have been installed to control NOx emissions.
ii)	Data on ambient air, stack and fugitive emission shall be regularly submitted online to Ministry's Regional Office at Bhubaneswar and Central Pollution Control Board as well as hard copy once in six months and display data on PM10, SO2 and NOx outside the premises at the appropriate place for the general public.	<ul> <li>Six Monthly compliance reports are sent in hard as well as soft copies to MoEF/ OSPCB. The same is also available at company web site.</li> <li>AAQ data is displayed at the entrance of the Plant (Plant's Main Gate) for information to general public through Electronic display board</li> <li>Four nos. of CAAQMS (Two Nos. inside and Two Nos. outside plant premises) are in operation.</li> <li>For monitoring of stack emissions, Online Continuous emission monitoring systems have been installed at all the operating units' viz. Coke Oven battery#2, Battery #1, CPP1, SP, BF, SMS, LCP and HSM and all are in operation.</li> </ul>
iii)	The National Ambient Air Quality Standard issued by the Ministry vide GSR No. 826(E) dated 16th November, 2009 shall be followed.	Air Quality standards conforming to NAAQS vide GSR 826 (E) has been referred for air quality monitoring and review.
iv)	The project proponent shall also submit six monthly reports on the status of the compliances of the stipulated environmental conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and SPCB. The Regional Office of the Ministry at Bhubaneswar/CPCB/SPCB shall monitor the stipulated conditions.	<ul> <li>We are submitting the six-monthly compliance report in stipulated time.</li> <li>Last Six-monthly compliance reports for the period Apr'17 to Sep'17 was submitted to MoEF/OSPCB Regional Office both in hard as well as soft copy on 01.12.17.</li> <li>Soft copy of the half yearly progress report was also been sent to roez.bsr-mef@nic.in.</li> </ul>
v)	The environmental statement for each financial year ending 31 march in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (protection Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliances of environmental conditions and shall also be sent to the respective Regional Offices of the MoEF by e-mail.	<ul> <li>Environment Statement for FY 2016 -17 was submitted to OSPCB on 25.09.2017 and the same for 2017-18 will be submitted before 30.09.2018.</li> <li>Both, Environment Statement and Status of Compliance of EC conditions have been uploaded on company's website. (www.tatasteel.com)</li> </ul>
vi)	The company shall submit within three months their policy towards Corporate Environment Responsibility which should inter-alia address (i) Standard operating process/ procedure to being into focus any infringement/ deviation/ violation of the environmental or forests norms/ conditions, (ii) Hierarchical system or Administrative order of the Company to deal with environmental issues and ensuring compliances to the environmental clearances conditions and (iii) system of reporting of noncompliance/ violation of environmental	<ul> <li>Corporate Environmental Policy was submitted to MoEF, New Delhi vide our letter no. TSL/DEL/805/2013 dated 8.1.2013.</li> <li>Copy of the same was also submitted to MoEF, Bhubaneswar Office.</li> </ul>

<b>Additional 10.10.2012</b>	Conditions	vide	letter	dated	Status as on 31.03.2018
norms to the and/or shareh	Board of Dir holders.	ectors	of the Co	ompany	

	Additional Safeguards vide letter dated	Compliance status as on 31.03.2018				
	13.5.2015					
2i	Project proponent should install 24x7 air and water monitoring devices to monitor the air emission and effluent discharge, as provided by Central Pollution Control Board (CPCB) and submit the report to Ministry and its Regional office	<ul> <li>To monitor the ambient air quality, 4 nos. of continuous ambient air quality monitoring station (CAAQMS) have been installed and are in operation.</li> <li>Continuous emission monitoring system (CEMS) have been installed at all the major stacks like Coke Battery No. 1 &amp; 2, Captive power plant, Sinter Plant, Blast Furnace, Steel Melting Shop, Lime Calcination Plant and Hot Strip Mill.</li> <li>Online Water quality monitoring stations installed at the outlet of BOD plant of Coke Oven Unit.</li> </ul>				
2ii	For Wet quenching: permission to start the coke ovens with wet quenching till CDQ is stabilized by June 2016, thereafter maintain wet quenching as a standby and use for 20 days (3 weeks) in a year or per annum for maintenance or operation exigencies	<ul> <li>CDQ unit for Battery No. 1 &amp; 2 is in operation.</li> <li>Wet quenching system is maintained as standby</li> </ul>				
2iii	For LDO: Use of LDO for generation of power in power plants and DG set till Blast Furnace gas is available for power generation in power plants and there after maintain LDO as "Standby" and use for 15 days(two weeks) per annum for maintenance or operational exigencies.	BF Gas generated is used for power generation in Captive Power Plant.  LDO is being maintained as standby fuel.  DG sets are operated only in case of exigencies.				
	Additional Conditions vide letter dated 20.12.2016	Compliance status as on 31.03.2018				
7.i	For Wet quenching: permission to start the coke ovens with wet quenching till the CDQ is stabilized by November 2016, thereafter maintain wet quenching as a standby and use for 20 days (3 weeks) in a year or per annum for maintenance or operational exigencies.	<ul> <li>CDQ unit for Battery No. 1 &amp; 2 is in operation.</li> <li>Wet quenching system is maintained as standby</li> </ul>				

#### AMBIENT AIR QUALITY (INSIDE PLANT)

Period: Oct'17 to March 2018

SI. No	Samplin g Stations	month	PM <sub>10</sub> μg /m³	PM <sub>2.5</sub> μg /m <sup>3</sup>	SO₂ µg / m³	NO <sub>x</sub> μg / m³	CO mg/m³	Ozone (O₃) μg/m³	Lead (Pb) μg/m³	Ammonia (NH₃) μg/m³	Benze ne (C <sub>6</sub> H <sub>6</sub> )	Benzo (a) Pyrene ng /m³	Arsenic (As) ng /m³	Nickel (Ni) ng/m³
1	Coke Oven		81.4	38.4	9.3	10.1	0.282	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
2	Power Plant		65.2	29.3	10.2	15.7	0.315	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
3	Gate-1	Oct'17 to	81.4	38.4	9.3	10.1	0.282	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
4	HSM	March'18	85.0	40.8	8.0	11.0	0.260	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
5	Gate No:4		86.5	41.5	9.8	10.5	0.263	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
6	SMS		80.1	38.4	7.3	10.0	0.238	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
C.P.C.B Standard		100 (24 Hrs.)	60 (24 Hrs.)	80 (24 Hrs.)	80 (24 Hrs.)	2 (8 Hrs.)	100 (8 Hrs.)	1 (24 Hrs.)	400 (24 Hrs.)	05 (Annua I)	01 (Annual)	06 (Annual)	20 (Annua I)	

### **Noise Monitoring Report**

Period: Oct'17 to March 2018

		Oct	t'17	Nov	/'17	Dec	c'17	Jar	ı'18	Feb	o'18	Marc	:h'18		Ave	rage	
SI. N	NOISE MONITORIN G LOCATIONS	in dBA (Day Time) 06.00a m to	in dBA (Night Time) 10.00p m to	in dBA (Day Time) 06.00a m to	NOISE STANDAR DS	in dBA (Night Time) 10.00p m to	NOISE STANDAR DS										
		10.00p m	06.00a m	10.00p m	Day time (in dBA)	06.00a m	Night time (in dBA)										
1	Sinter Plant	66.6	52.4	61.2	52.7	61.9	51.7	62.9	56.8	61.4	50.6	66.8	53.6	63.5	75	53.0	70
2	Blast Furnace	61.1	47.6	58.3	49.6	55.4	50.2	58.3	50.1	58.4	49.3	59.5	46.7	58.5	75	48.9	70
3	SMS	52.3	44.8	52.8	41.2	54.8	49.9	48.2	46.9	62.9	47.8	49.7	48.8	53.5	75	46.6	70
4	Gate-1	61.6	52.4	54.3	51.8	59.3	50.2	62.1	49.1	63.2	53.8	61.4	52.6	60.3	75	51.7	70
5	RMHS	62.9	50.5	61.9	49.5	63.9	51.6	66.3	48.8	63.1	49.2	58.8	49.4	62.8	75	49.8	70
6	HSM	58.4	47.5	55.8	46.8	56.4	52.3	58.1	44.7	59.9	49.4	53.7	47.2	57.1	75	48.0	70
7	LCP	62.2	48.6	53.4	46.3	57.7	49.9	59.8	50.4	58.2	48.8	60.1	48	58.6	75	48.7	70

### GROUND WATER QUALITY Period: Oct'17 to March 2018

SI. No.	Parameter	Standard as per BIS: 10500	Apr'17	May'17	Jun'17	Jul'17	Aug'17	Sept'17	Average
1	pH Value	6.5-8.5	6.6	6.8	7.1	6.5	6.8	6.6	6.73
2	Colour	5	CL	CL	CL	CL	CL	CL	CL
3	Odour	U/O	U/O	U/O	U/O	U/O	U/O	U/O	U/O
4	Taste	Agreeable	AL	AL	AL	AL	AL	AL	AL
5	Turbidity (NTU), max	5	0.22	0.3	0.61	0.44	0.48	0.73	0.46
6	Anionic Detergents, mg/l, max	0.2	ND	ND	ND	ND	ND	ND	ND
7	Aluminium as Al, mg/l, max	0.03	BDL	BDL	BDL	BDL	BDL	BDL	BDL
8	Alkalinity , mg/l, max	200	93	73	67	78	73	81	77.50
9	Total Hardness (as CaCO₃), mg/l, max	300	73.2	80.4	71.7	91	81.7	70.9	78.15
10	Electrical Conductivity at 25°C, μmho/cm	\$	183	264	173	217	211	209	209.50
11	Calcium (as Ca), mg/l, max	75	11.6	14.2	12.9	16.3	18.5	13.7	14.53
12	Magnesium as Mg, mg/l, max	\$	7.8	5.8	9.1	10.4	11.8	6.3	8.53
13	Sodium as Na, mg/l, max	\$	9.1	8.3	6.6	5.2	9.9	8.7	7.97
14	Potassium as K, mg/I, max	\$	0.32	0.32	0.36	0.53	0.68	0.31	0.42
15	Copper (as Cu), mg/I, max	0.05	BDL	BDL	BDL	BDL	BDL	BDL	BDL
16	Iron (as Fe), mg/l, max	0.3	0.16	0.23	0.11	0.43	0.38	0.39	0.28
17	Manganese (as Mn), mg/l, max	0.1	BDL	BDL	BDL	BDL	BDL	BDL	BDL
18	Chloride (as Cl), mg/l, max	250	6.6	12.9	14.8	11.2	13.3	15.3	12.35
19	Sulphate (as SO <sub>4</sub> ), mg/l, max	200	22.8	22.9	21.8	22.3	28	21.6	23.23

SI. No.	Parameter	Standard as per BIS: 10500	Apr'17	May'17	Jun'17	Jul'17	Aug'17	Sept'17	Average
20	Nitrate (as NO₃), mg/l, max	45	0.11	0.26	0.27	0.36	0.28	0.33	0.27
21	Fluoride (as F), mg/l, max	1	0.04	0.09	0.11	BDL	0.1	0.12	0.09
22	Phenolic Compounds (as C <sub>6</sub> H <sub>5</sub> OH), mg/l, max	0.001	BDL	BDL	BDL	BDL	BDL	BDL	BDL
23	Mercury (as Hg), mg/l, max	0.001	BDL	BDL	BDL	BDL	BDL	BDL	BDL
24	Cadmium (as Cd), mg/l, max	0.01	BDL	BDL	BDL	BDL	BDL	BDL	BDL
25	Selenium (as Se), mg/l, max	0.01	BDL	BDL	BDL	BDL	BDL	BDL	BDL
26	Arsenic (as As), mg/l, max	0.05	BDL	BDL	BDL	BDL	BDL	BDL	BDL
27	Cyanide (as CN), mg/l, max	0.05	BDL	BDL	BDL	BDL	BDL	BDL	BDL
28	Lead (as Pb), mg/l, max	0.05	BDL	BDL	BDL	BDL	BDL	BDL	BDL
29	Zinc (as Zn), mg/l, max	5	0.12	0.18	0.41	0.48	0.21	0.08	0.25
30	Nickel as Ni, mg/l, max	\$	BDL	BDL	BDL	BDL	BDL	BDL	BDL
31	Total Chromium as Cr, mg/l, max	\$	0.08	0.16	0.16	BDL	0.22	0.15	0.15
32	Chromium (as Cr+6), mg/I, max	0.05	0.006	0.004	0.005	0.004	0.006	0.008	0.01
33	Mineral Oil, mg/l, max	0.01	ND	ND	ND	ND	ND	ND	ND
34	Total Coliform, MPN/ 100 ml	\$	ND	ND	ND	ND	ND	ND	ND
35	E-coli , MPN/ 100 ml	\$	ND	ND	ND	ND	ND	ND	ND
36	Total Dissolved Solids, mg/l, max	500	190	166	148	166	171	133	162.33
37	Residual, free Chlorine, mg/l, min	0.2	ND	ND	ND	ND	ND	ND	ND
38	Boron mg/l, max	1	BDL	BDL	BDL	BDL	BDL	BDL	BDL

### Six Monthly Compliance Status (Oct'17 to Mar'18) of Environmental Clearance including Amendment in EC for 6.0 MTPA Integrated Steel Plant at Kalinganagar, Duburi, District-Jajpur

7<sup>th</sup> Nov 2006, 10<sup>th</sup> Oct 2012, 13<sup>th</sup> May 2015 and 20<sup>th</sup> Dec 2016

#### **VOC Monitoring Report of Coke Oven**

#### (Monthly average from Oct'17 to March'18)

SI. No	Monitoring Location	month	Benzene (C <sub>6</sub> H <sub>6</sub> )	Benzo (a) Pyrene ng /m³
1	Coke Oven Plant		1.42	0.11
2	Near Coke Oven Battery#1	Oct'17 to March'18	<2.0	0.18
3	Near Coke Oven Battery#2		<2.0	0.14
4	Near CDQ Area		<2.0	BDL
	C.P.C.B Stan	dard	05 μg/m³ (Annual)	01 ng/m³ (Annual)

---X---