S1.No.	Condition	Compliance Status
D1.110.		Compilation Status
i.	The gaseous emissions from various process units shall conform to the load/mass based standards notified by this Ministry on 11th May, 1993 and standards prescribed from time to time. The state Board may specify more stringent standards for the relevant parameters keeping in view the nature of the industry and its size and location. At no time, the emission level shall go beyond the prescribed standards. Interlocking facilities shall be provided so that process can be automatically stopped in case emission level exceeds the limit.  Efforts shall be made to reduce RSPM levels in the ambient air and a time bound action plan shall be submitted. On-line stack monitoring facilities for all the stacks including new sinter	All the existing and new units ar provided with adequate pollutio control equipment (PCEs) to ensure the emission levels within specific legal requirement.  Please refer <b>Annexure – I</b> for monitoring reports for April 201 to March 2017. Alarms an interlocking wherever possibly have been provided in the unit to indicate emission level.  • We have submitted Actional Plan and status update on reduction of RSPM Level in Ambient Air vide our letter.
	plant and power house and sufficient air pollution control devices shall be provided to keep the emission levels below 50 mg/Nm³ and reports submitted to the Jharkhand SPCB and CPCB.	<ul> <li>June 22, 2013.</li> <li>Online stacks monitoring systems in the major stacks have been installed.</li> <li>All the new Air Pollution Control devices have been commissioned with design emission levels of below 50 mg/Nm³ of particulate matter from stacks within Works.</li> <li>Monitoring reports are being submitted regularly.</li> </ul>
iii.	In-plant control measures for checking fugitive emissions from all the vulnerable sources shall be provided. Dust extraction system and dry fogging system will be provided to control air emissions at material transfer and sizing plants. ESP and bag filters shall be provided wherever required to keep the emission levels below 50	<ul> <li>The status of control measures in the units are as follows.</li> <li>Installed ESPs and Bag Houses in the "H" Blast Furnace, Sinter Plant#4.</li> <li>Dust control systems, dry fog system and water spraying have been provided at the material handling systems.</li> <li>Low NOx burners have been</li> </ul>

dated April 16, 2007	
mg/Nm³ particularly in 'H'-BF stock house, BF cast houses and Sinter stock house. Low NO burners will be installed to control NO emissions. Gas cleaning plant shall be provided to BF. Further, specific measures like water sprinkling shall be carried out and fugitive emissions shall be controlled, regularly monitored and records maintained.	<ul> <li>installed.</li> <li>The following control measures are in place to check the fugitive emissions.</li> <li>Bag Houses, water-spraying arrangements are provided at all potential dust generating points.</li> <li>The boilers at Power House#3 have been converted to gas firing from coal. This has contributed significantly in the reduction of the fugitive emissions.</li> <li>Regular cleaning of shop floor area with the help of mechanical dust collector, road sweepers, is being done.</li> <li>Monitoring of fugitive emission is being done at the regular intervals and records kept.</li> <li>Please refer <b>Annexure</b> - <b>I</b> for monitoring reports for April 2016</li> </ul>
iv. Gaseous emission levels including secondary fugitive emissions shall be controlled within the latest permissible limits issued by the Ministry and regularly monitored. Guidelines / Code of Practice issued by the CPCB in this regard shall be followed.	to March 2017.  All the Steel Melting Shops (LD#1, LD#2 and LD#3) have been provided with Electrostatic Precipitators (ESP) as secondary emission control system.
v. Total water requirement from River Subarnarekha shall not exceed 3,91,800 m³/day as per the permission accorded by the State Govt. No ground water shall be used. GCP wastewater treatment plants for 'H'-BF and Billet Caster no. 3 shall be provided. The treated process effluent shall be recycled and reused in cooling tower as well as for green belt development. Cooling tower blow down shall be used for granulation, coke quenching, dust suppression	Subarnarekha River for steel making as make-up water is within the recommended capacity by State Government.

uateu 1	April 16, 2007	
vi.	and other non-product uses. Treated effluent discharge into the streams/river shall not exceed 37,000 m³/day. Domestic effluent shall be treated in Sewage Treatment Plant (STP).  Continuous monitoring of Total Organic Compounds (TOC) shall be done at the outlet of ETP	the prescribed standard.  • Sewage from the Jamshedpur Town is treated in Sewage Treatment Plants (2 nos.). BOD and Suspended Solids are within the prescribed limits.  Online TOC analyzer has been installed for continuous monitoring at BOD Plant Outlet.
vii.	(BOD plant).  Ground water monitoring around the solid waste disposal site / secured landfill (SLF) shall be carried out regularly and report submitted to the Ministry's Regional Office at Bhubaneswar, CPCB and OPCB.	We are regularly conducting the ground water monitoring around the waste disposal site at five locations. Analysis report submitted to JSPCB indicates that concentration of heavy meals is well within the prescribed limits.  Please refer <b>Annexure</b> – <b>I</b> for
viii.	Solid wastes shall be reused in the cement plant, road construction and railway ballast. BF slag shall be granulated in cast house and used for cement making. LD slag shall be processed in Waste Recycling Plant and subsequently recycled in the BF LD sludge and sinter plants. Remaining slag shall be used for road construction and filling the low-lying areas. The Chrome sludge in the form of Cr+3 shall be dumped only in the secured landfill located within the plant premises and proper disposal of Chrome sludge shall be ensured. Oily waste shall be burnt in the	<ul> <li>monitoring reports for April 2016 to March 2017.</li> <li>BF slag from H Blast Furnace is granulated in cast house and is used for cement making.</li> <li>LD slag is processed at the modernized Waste Recycling Plant to recover the metallic portion and reuse at Sinter Plants.</li> <li>The chrome sludge from CRM Plant is stored in secured land fill within the Works.</li> <li>Oily sludge is burnt in the Incinerator.</li> </ul>
ix.	incinerator.  Fly ash shall be used in cement plants. Bottom ash shall be disposed off in a suitably designed landfill as per CPCB guidelines to prevent leaching to the sub-soil and underground	All boilers at Tata Steel are capable to fire gas. This has resulted in considerable reduction in generation of fly ash. To deal with emergency situations; a small amount of

dated April 16, 2007

uateu A	April 16, 2007	
x.	Practice of disposal of solid wastes along the river shall be immediately stopped and efforts shall be made to remove the solid waste from the banks of	coal firing is done occasionally in boiler # 4 at PH#4. Fly ash generated from Power House#4, which is less in quantum, is stored in Bara Ash Pond.  No disposal of solid waste along the river bank from Tata Steel.
	the river.	
xi.	A time bound action plan should be submitted to reduce solid waste, its proper utilization and disposal. Action plan for the reclamation of Jugsalai Muck disposal site submitted to the Ministry shall be implemented in a time bound manner.	An action plan for Solid waste management has been submitted to JSPCB vides our letter no. EMD/C-02/460/11 dated December 16, 2011.  We have also submitted road map regarding future generation and the disposal of solid waste vide our letter no. EMD/C-33/124/13 dated June 22, 2013.  Tata Steel has taken a number of steps to improve the solid waste utilization. For the period during April 2016 to March 2017, the solid waste utilization was 81.9% excluding storage of LD slag at Galudih for processing. Various actions have been already planned to improve the solid waste utilization further.  The reclamation of JMD has been completed. A rainwater harvesting facility has been constructed at the top of the JMD which is being utilized for development of greenery. Besides this, there is a provision to pump surface drainage carry out from the plant to JMD area for
		development of greenery.
xii.	The company shall develop surface as well as ground water harvesting structures to harvest the rainwater for utilization in the lean season besides recharging the ground water	<ul> <li>Rainwater is collected from the new facilities through surface drain into Cooling Pond. The rainwater thus collected is recycled in the plant for reuse.</li> <li>The rainwater harvesting</li> </ul>

dated April 16, 2007

	<b>April 16, 2007</b> table.	structures at four buildings
	table.	within and outside the plant
		have been completed.
xiii.	Green belt shall be developed in 1157.7 ha (33 %) out of total 4391.85 ha. within and around the plant premises as per the CPCB guidelines in consultation with DFO.	We have planted approx. 60,801 saplings during April 2016 to March 2017 inside the works and Jugsalai Muck Dump area and in Township. Every year plantation done in available space. The following plant species are being planted: Ficus, karanj, Cicilipinia, Palm, Ashoka, Mahogany, Caesalpinia Arjun, Sita Ashok, Bakul, Spathodia, Kanchan, Jural, Tabulia, Sissam, Termanelia Sp.,Arica palm, foxtail palm, Tecoma, Kannel, Tababia, Ghandhraj, calendra, Tagar, Hemelia, Kamani, Karbi, Calendra
xiv.	Occupational Health Surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	etc. The health surveillance is being done as per Factory Act. Records are maintained at the Occupational Health Services.
xv.	Recommendations made in the Corporate Responsibility for Environment Conservation (CREP) issued for the steel plants shall be implemented.	CREP recommendations have been implemented.
	General Conditions	
i.	The project authorities must strictly adhere to the stipulations made by the Jharkhand Pollution Control Board (Jharkhand SPCB) and the State Government	by JSPCB and State Government
ii.	No further expansion or modifications in the plant should be carried out without prior approval of the Ministry of Environment and Forests.	expansion from 6.8 MTPA to 9.7 MTPA Steel Plant was granted

dated A	pril 16, 2007	
		11011/691/2007-IA. (II) dated March 1, 2016.
		Necessary Environment Clearance will be taken before any further expansion or modification.
iii.	At least four ambient air quality monitoring stations shall be established in the downward direction as well as where maximum ground level concentration of SPM, SO <sub>2</sub> and NO <sub>x</sub> are anticipated in consultation with the Jharkhand SPCB. Data on ambient air quality and stack emission should be regularly submitted to this Ministry including its Regional Office at Bhopal and the Jharkhand SPCB/CPCB once in six months.	Monitoring Stations have been installed. We submit monitoring data on ambient air quality and stack emission regularly to
iv.	Industrial wastewater shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 11 <sup>th</sup> May, 1993 and 31 <sup>st</sup> December, 1993 or as amended form time to time. The treated wastewater shall be utilized for plantation purpose.	Wastewater is being treated in the Effluent treatment plants of respective units for meeting the standards. Treated wastewater is used for plantations and road dust suppression. Most of treated wastewater is recycled back to the system.
V.	The overall noise levels in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75 dBA (daytime) and 70 dBA (nighttime).	The control measures such as silencers, enclosures, hoods, rubber pads, have been provided at the appropriate places on all sources of noise generation in the plant. The ambient noise level is being monitored. Please refer <b>Annexure – I</b> for monitoring reports for April 2016 to March 2017.
vi.	The project proponent shall also comply with all the environmental protection	• Implementation of protection measures as indicated in the EIA for 6.8 MTPA plant units

dated A	pril 16, 2007	
	measures and safeguards recommended in the EIA and EMP report. Further, the company must undertake socioeconomic development activities in the surrounding villages like community development programs, educational programs, drinking water supply and health care etc.	have been complied which includes ESPs, bag filters, online slag granulation system for blast furnaces and waste water treatment plants etc.  • Socio economic development activities are regularly undertaken in and around Jamshedpur through the two agencies namely, Tata Steel Rural Development Society and Tata Steel Community Development and Welfare Services Centers. The development activities undertaken in the surrounding community are need based and are in the field of health care, education, midday meal at schools, sports and culture, self-employment, drinking water, rural electrification, etc. Tata Steel also facilitate the Institutes like R D Tata Technical Institute, Tata Football Academy, Tata Archery Foundation, etc. which encourages the local talent to develop themselves and participate at National and International levels.
vii.	As mentioned in the EIA and EMP, ₹ 259.00 Crores and ₹18.5 Crores earmarked towards the capital cost and recurring cost/annum for environmental pollution control measures shall be judiciously utilized to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government. The funds so provided shall not be diverted for any other purpose.	The funds for capital investment on pollution control equipment were not diverted. The 6.8 MTPA project has been completed. All the pollution control equipment have been commissioned and are being operated and maintained regularly.
viii.	The Regional Office of this Ministry at Bhubaneswar/ CPCB/Jharkhand SPCB will	Six monthly compliance reports and the monitored data are being submitted regularly. Please refer

	April 10, 2007	
	monitor the stipulated	
	conditions. A six monthly	± ±
	compliance report and the	2017.
	monitored data along with	
	statistical interpretation shall be	
	submitted to them regularly.	
ix.	The Project Proponent shall	The Notice has been advertised in
	inform the public that the	two local newspapers <i>viz.</i>
	project has been accorded	Uditvani (Hindi) and Avenue Mail
	environmental clearance by the	(English) on April 21, 2007 and
	Ministry and copies of the	
	clearance letter are available	also sent to the MoEF vide our
	with the OSPCB/Committee and	letter no. EMD/C-32/2118/07
	may also be seen at Website of	dated August 18, 2007.
	the Ministry of Environment and	5 ,
	Forests at <a href="http://envfor.nic.in">http://envfor.nic.in</a> .	
	This shall be advertised within	
	seven days from the date of	
	issue of the clearance letter, at	
	least in two local newspapers	
	that are widely circulated in the	
	region of which one shall be in	
	the vernacular language of the	
	locality concerned and a copy of	
	the same shall be forwarded to	
	the Regional office.	
х.	Project authorities should	It has been complied as the
	inform the Regional Office as	project has already been
	well as the Ministry, the date of	1 0
	financial closure and final	
	approval of the project by the	
	concerned authorities and the	
	date of commencing the land	
	development work.	
L	acveropinent work.	