

TSL/SPCB/BS-03/2023-18/373 September 21, 2023

The Member Secretary
State Pollution Control Board, Odisha
Parivesh Bhawan, A/118,
Nilakantha Nagar, Unit-VIII,
Bhubaneswar-751 012

Subject: Environmental Statement for the financial year 2022-23 for Tata Steel Ltd.

Meramandali, Dhenkanal.

Reference: Consent Order No.4463/IND-I-CON-5440 dated 23.03.2023

Dear Sir,

In reference to the captioned subject and letter cited above, we are submitting herewith "Annual Environmental Statement (Form-V)" duly filled in the prescribed format for the 5.6 MTPA crude steel production at integrated steel plant of Tata Steel Ltd. At: Narendrapur, Via: Meramandali, Dist.: Dhenkanal, Odisha, for the financial year 2022-23.

This is for your kind information and necessary record please.

Thanking you,

Yours faithfully,

For Tata Steel Limited

Anoop Srivastava

Chief Environment, TSM

Encl: As above

Copy to: 1. The Regional Officer, Odisha State Pollution Control Board, Angul, Odisha.

2. Deputy Director General, MoEF&CC, Integrated Regional Office (EZ), A/3, Chandrashekarpur, Bhubaneswar-751023.

2 5 SEP 2023

TATA STEEL LIMITED

# [FORM-V] (See rule 14 of The Environment Protection Act, 1986) Environment Statement for the financial year ending 31 March 2023

# PART – A

	General Infor	mation
	Name of the Company	Tata Steel Limited, Meramandali
1.	Name & Address of the owner/occupier of the industry, operation or process	Sri Thachat Viswanath Narendran, CEO& MD Tata Steel Limited, Meramandali At: Narendrapur, PO: Kusupanga Via: Meramandali, Dist.: Dhenkanal, Pin: 759121, Odisha
2.	Industry Category	Red-A
	Primary (STC Code), Secondary (STC Code)	Large Metallurgical Industry Integrated Iron & Steel Industry
3.	Production capacity-Units	Production Capacity: 5.6 MTPA Crude Steel.  Production During 2022-23: 4.952 Million Tons Crude Steel.  (Major units are: RMHS & RMPP, Blast Furnaces, Coke Ovens, Sinter Plants, SMS, BOF, HSM, CRM, Captive Power Plant, Industrial By-Product Management Division and Utilities including Air Sepretaion Units.)
4.	Year of establishment	2006
5.	Date of last environment statement submitted	September 29, 2022 vide letter no.TSL/SPCB/BS-03/2022-14/249

# <u>PART – B</u>

Water & Raw	material Consumption				
1: Total Water Consumption (m³/d)					
Water Consumption	During the previous Financial Year (2021-22)	During the current Financial Year (2022-23)			
Industrial Consumption (Inside Works as Makeup water)	54,185	52,283			
Domestic Consumption (Inside Works as Drinking water)	3,054	4,243			
2: Water Consumption per unit of the p	roduct (m³/tcs)	CONTROL OF A STATE STATE STATE STATE A			
Name of the Products : Crude Steel	Process fresh water consumption per unit of				
	2021-22	2022-23			
Specific fresh Water Consumption	3.42	3.55			

3: Raw Material Consumptio	n (Works):					
	Name of	Consumption of raw material per unit of product (MT/tcs)				
Name of Raw materials	Products	During the previous Financial Year (2021-22)	During the current Financial Year (2022-23)			
Iron (Lump &Fine)		1.31	1.31			
Purchase Pellet		0.28	0.37			
Limestone & Dolomite		0.28	0.36			
Quartz		0.03	0.02			
Coking Coal		0.25	0.54			
Non-Coking coal		0.65	0.48			
Scrap	Crude Steel (Slab/Billet)	0.07	0.06			
Ferro-Chromium	(Glab/blilet)	0.0002	0.0001			
Ferro-Manganese		0.0026	0.0022			
Ferro-Silicon		0.0002	0.0002			
Silico-Manganese		0.0008	0.0006			
Znic		0.001	0.001			
Znic Alloy (Premix)		0.0008	0.0007			

# PART – C Pollution discharged to Environment per unit of Output (Parameters as specified in the Consent issued)

(i) Works:					
Pollutants		f pollutants I (mass/day)	pollutants	trations of discharged /volume)	% of variation from prescribed standards
	(Ton	s/day)	(n	ng/l)	In % age (referring CTO)
(a) Water	2021-22	2022-23	2021-22	2022-23	2022-23
TSS	0.24	0.189	42	63.13	(-) 37 %
COD	0.448	0.132	78	43.99	(-) 82.4 %
Ammonia as N	0.0001	0.007	0.01	2.48	(-) 95 %
BOD	0.01	0.009	0.9	3.11	(-) 90 %
Phenols	0.0001	Less than 0.0015	0.009	Less than 0.5*	(-) 50 %
Total Cyanide as CN	0.0002	Less than 0.0003	0.03	Less than 0.1*	(-) 50%
	2021-22	2022-23	2021-22	2022-23	2022-23
(b) Air	Tons	s/day	mg/	/Nm3	In % age (referring CTO)
PM	8.30	6.87	19.71	17.59	(-) 65 %
SO2	60.55	50.87	508	381	(-) 37 %

NOx	20.94	21.03	126	142	(-) 68 %
L	·	A1 CAMBONIC CONTRACTOR OF THE		CONTRACTOR CONTRACTOR AND A PROGRAMMENT OF THE ANALYSIS OF THE ANALYSIS AND A STREET AND A STREET AND A STREET AND A STREET AS A STREET AND A STREET AND A STREET AS A STREET AND A STREET AS A STREET	

<sup>\*</sup>Detection Limit for Phenols and Cyanide is 0.5 and 0.1 respectively.

1. Surface Water Quality

Parameter	Unit	Kisind	a Nalla	Lingra	a Nalla
i diameter	Ome	U/S	D/S	U/S	D/S
pH Value	obert a black and a second and a	6.95 - 8.11	6.82 - 8.21	7.66 - 8.21	7.1 - 8.33
Colour	Hazen	BDL (DL:1.0)	BDL (DL:1.0)	BDL (DL:1.0)	BDL (DL:1.0)
Temperature	Deg C	25 - 31	25 - 33	25 - 29	24 - 25
Total Suspended Solids	mg/l	3.2 - 20.4	2 - 26.8	< 14.8	< 26
Ammoniacal Nitrogen	mg/l	Mag (	-	BDL (DL:0.1)	BDL (DL:0.1)
Arsenic as As	mg/l	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)
BOD, 3days at 27°C	mg/l	BDL (DL:2.0)	< 3.4	BDL (DL:2.0)	< 2.7
Boron as B	mg/l	BDL (DL:0.25)	BDL (DL:0.25)	BDL (DL:0.25)	BDL (DL:0.25)
Cadmium as Cd	mg/l	BDL (DL:0.001)	BDL (DL:0.001)	BDL (DL:0.001)	BDL (DL:0.001)
Calcium as Ca	mg/l	40 - 110.88	11.88 - 54.88	31.68 - 48	28 - 102.96
Chlorides as Cl	mg/l	24.74 - 89.97	14.7 - 146.4	19.59 - 49.98	14.11 - 119.96
COD	mg/l	7.2 - 16.7	6.98 - 15.4	6.85 - 12	7.2 - 16
Copper (as Cu)	mg/l	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)
Cyanide as CN	mg/l	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)
Fluoride as F-	mg/l	0.35 - 4.7	0.22 - 2.4	0.24 - 1.06	0.33 - 2.17
Free Ammonia	mg/l		-	BDL(DL:0.1)	BDL(DL:0.1)
Hexa Chromium as Cr <sup>+6</sup>	mg/l	0 - 0.052	< 0.088	< 0.032	BDL (DL:0.01)
Iron as Fe	mg/l	0.09 - 0.89	0.06 - 2.01	0.11 - 0.38	0.08 - 1.58
Lead (as Pb)	mg/l	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)
Manganese (as Mn)	mg/l	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)
Mercury (as Hg)	mg/l	BDL (DL:0.0002)	BDL (DL:0.0002)	BDL (DL:0.0002)	BDL (DL:0.0002)
Nickel (as Ni)	mg/l	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)
Nitrate as N	mg/l	0.52 - 1.02	0.61 - 1.01	0.5 - 0.92	0.62 - 1.45
O&G	mg/l	BDL (DL:1.4)	BDL (DL:1.4)	BDL (DL:1.4)	BDL (DL:1.4)
Phenolic Comp	mg/l	BDL (DL:0.001)	BDL (DL:0.001)	BDL (DL:0.001)	BDL (DL:0.001)
Phosphate as P	mg/l	0.09 - 0.46	0.07 - 0.62	< 0.32	< 0.4
RFC	mg/l	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)
Selenium (as Se)	mg/l	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)
Sulphate mg/l	mg/l			BDL(DL:0.02)	BDL(DL:0.02)
TKN	mg/l	BDL (DL:0.3)	BDL (DL:0.3)	BDL (DL:0.3)	BDL (DL:0.3)
Total Chromium (as Cr)	mg/l	••	-	BDL(DL:0.01)	BDL(DL:0.01)
Total Nitrogen Content	mg/l	Page	_	0.84 - 3.6	1.02 - 5.1
Vanadium (as V)	mg/l		***	BDL(DL:0.05)	BDL(DL:0.05)

I				·	
Zinc (as Zn)	mg/l	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)

NB: U/S: Upstream; D/S: Downstream; BDL: Below Detection Limit; DL: Detection Limit 2. ETP Treated Water Quality

Parameter	UOM	BOD-1	Treated 6	effluent	BOD-2 Treated effluent			
rarameter	JOIVI	Min	Max	Avg	Min	Max	Avg	
рН	_	7.3	8.3	7.7	6.6	7.7	7.0	
Total Suspended Solid	mg/l	6.8	90.0	48.8	32.0	78.0	51.0	
Oil & Grease	mg/l	4.0	7.0	4.9	5.0	6.0	5.3	
Chemical Oxygen Demand (COD)	mg/l	28.0	220	165	64.00	240	164	
Biochemical Oxygen Demand (BOD)(27 ° C for 3 days)	mg/l	7.2	28.6	22.0	13.00	29.0	22.2	
TCN	mg/l	0.10	0.15	0.12	0.07	0.18	0.12	
Phenol	mg/l	0.49	0.93	0.69	0.65	0.88	0.73	

Parameter	UOM		ETP-1	TO TO THE REAL PROPERTY OF THE PARTY OF THE	ETP-2		
r drameter	OCIVI	Min	Max	Avg	Min	Max	Avg
рН	-	7.3	8.3	7.8	6.6	8.1	7.4
Total Suspended Solid	mg/l	5.4	65.0	39.0	5.6	72.0	38.2
Oil & Grease	mg/l	<5	<5	<5	<5	<5	<5
Chemical Oxygen Demand (COD)	mg/l	20.0	80.0	39.4	25.6	68.0	43.6
Biochemical Oxygen Demand (BOD)(27 ° C for 3 days)	mg/l	4.3	8.8	6.5	4.7	9.2	6.6
Iron as Fe	mg/l	0.1	0.5	0.2	0.1	0.5	0.2

Parameter	UOM		ETP-3		CRM ETP		
1 didilicter	OOM	Min	Max	Avg	Min	Max	Avg
рН	_	6.5	8.1	7.4	6.4	7.7	6.9
Total Suspended Solid	mg/l	29.0	64.0	39.8	16.0	66.0	41.3
Oil & Grease	mg/l	<5	<5	<5	<5	<5	<5
Chemical Oxygen Demand (COD)	mg/l	31.2	76.0	54.3	100.0	188.0	154.0
Biochemical Oxygen Demand (BOD)(27 ° C for 3 days)	mg/l	4.7	10.7	8.1	16.7	28.0	22.7
Iron as Fe	mg/l	0.1	0.2	0.2	0.1	1.3	0.3

# 3. Sewage Treatment Plant -Treated outlet quality

Parameter	HOM	OM BF-1 STP			SMS-1 STP			AEL STP			Colony STP		
	COIVI	Min	Max	Avg	Min	Max	Avg	Min	Max	Avg	Min	Max	Avg
рН	-	7.2	8.2	7.9	7.6	8.3	7.9	7.2	8.0	7.6	7.0	8.3	7.5
TSS	mg/l	23.0	67.0	36.5	24.0	68.0	40.4	17.0	58.0	42.6	22.0	74.0	39.6
BOD	mg/l	8.0	23.0	13.8	11.1	21.0	14.4	10.0	24.0	16.5	7.2	22.0	15.0

# 4. Plant Discharge Water Quality Analysis report.

Parameter	UOM	Disch	narge to L	₋ingra	Discharge to Kisinda			
i arainetei	UCIVI	Min	Max	Avg	Min	Max	Avg	
pH	-	6.63	8.39	8.13	7.84	8.23	8.08	
Total Suspended Solid	mg/l	51.19	80.00	70.0	44.52	77.88	56.0	
Oil & Grease	mg/l	<4.0	<4.0	<4.0	<4.0	<4.0	<4.0	
Chemical Oxygen Demand (COD)	mg/l	37.00	64.80	50.2	29.71	47.92	39.4	
Biochemical Oxygen Demand (BOD)(27 ° C for 3 days)	mg/l	2.69	3.63	3.2	2.47	3.48	3.0	
Phenol	mg/l	<0.5	0.57	<0.5	<0.5	<0.5	<0.5	
Ammonia	mg/l	2.01	6.25	4.19	0.40	1.40	0.77	
Total Cyanide	mg/l	<0.1	0.13	<0.1	<0.1	<0.1	<0.1	

## 4. Ambient Air Quality

Parameters	UoM Norn		C.	AAQMS	5-1	С	AAQMS	S-2	C	AAQMS	5-3
r arameters	COIVI	NOTH	Min	Мах	Avg	Min	Max	Avg	Min	Max	Avg
PM10	μg/m³	100	15.4	128.5	71.7	37.4	211.0	126.3	27.1	143.4	74.3
PM2.5	μg/m³	60	6.6	78.2	37.8	12.0	87.6	49.8	8.5	58.7	31.1
SO <sub>2</sub>	μg/m³	80	11.5	14.2	12.6	11.4	29.1	17.8	9.2	25.7	12.8
$NO_2$	μg/m³	80	5.5	16.1	13.6	9.2	12.7	10.0	16.9	23.7	18.7
CO	mg/m³	2	0.2	0.7	0.55	0.3	0.9	0.64	0.3	0.9	0.42

Parameters	UoM Norm		eters HoM Norm CAAQMS-4		CAAQMS-5			CAAQMS-6			
1 arameters	COIVI	NOTH	Min	Max	Avg	Min	Max	Avg	Min	Max	Avg
PM10	µg/m³	100	58.1	192.8	102.6	31.0	153.0	84.4	55.9	207.5	122.0
PM2.5	μg/m³	60	21.0	78.9	43.9	14.9	118.4	50.8	21.8	106.8	45.7
SO <sub>2</sub>	μg/m³	80	5.6	10.1	6.9	7.6	22.2	12.7	5.7	32.5	16.5
NO <sub>2</sub>	µg/m³	80	8.9	24.6	20.5	6.4	24.9	17.5	12.0	29.2	20.0
CO	mg/m³	2	0.2	0.6	0.36	0.4	1.1	0.61	0.4	0.9	0.66

Parameters	I I O N/I	UoM Norm		CAAQMS-7			
rafameters	COIVI	NOTH	Min	Max	Avg		
PM10	μg/m³	100	59.8	258.7	129.4		
PM2.5	μg/m³	60	23.0	102.8	52.1		
SO <sub>2</sub>	μg/m³	80	8.2	24.1	15.8		
NO <sub>2</sub>	μg/m³	80	22.7	33.1	31.0		
CO	mg/m³	2	1.1	1.2	1.16		

CAAQMS 1: Near Township; CAAQMS 2: Near AEL Boundary; CAAQMS 3: Near CRM; CAAQMS; 4: Near Water Complex; CAAQMS 5: Near Coke Oven 2; CAAQMS 6: Near Wagon Tippler; CAAQMS 7: Near Material Gate Values are derived from 24 hourly average data except CO values are derived from 8 hourly average data.

### PART - D

Hazardous Wastes (As specified under The Hazardous and Other Wastes (Management & Transboundary Movement) Rules, 2016)

Movement	<i>j</i> ixuics, 2010)	
	Total Qua	antity (MT)
Hazardous waste	During the previous Financial Year (2021-22)	During the current Financial Year (2022-23)
(a) From Process		
Used/ Spent Oil	295	256
Waste residue containing oil	25.9	36.7
Spent Ion Exchange Resin	3.0	0
Rejected Chemical Container	18.2	5957 Nos. & 20.18 MT
Insulation Material	114	85
Alkali Residue	23	12.1
Oily Sludge	102	122
Zinc Ash & Zinc Dross	471	510
Spent Solvent (Waste Thinner - Oily Waste)	39.63	3.95
(b) From Pollution Control Facilities	Annual Review of the Control of the	
BOD plant Sludge	2497	2457
Decanter Tar Sludge	1396	1499
ETP Sludge/Chemical Sludge from wastewater treatment plant	694	780
Exhaust Air or Gas cleaning residues	179882	188566

NB: Exhaust Air or Gas cleaning residues: GCP sludge of BF & BOF, FES dust & bag filter dust of SMS, and Exhaust air of BF.

# PART - E

### **Solid Wastes**

# **Total Quantity Generated**

	Total Quantity Generated (MT)			
Name of the Waste	During the previous Financial Year (2021-22)	During the current Financial Year (2022-23)		
(a) From Process				
1. Char	186697	162983		
2. BF Slag	1754865	1847873		
3. SMS Slag	882264	871195		
4. Bottom Ash	38583	33669		
(b) From Pollution Control Facilities	Annual of the state of the stat			
1. Fly Ash	347253	324752		
<ol><li>APC Dust (ESP, Bag filter Dust, DRI ESP dust, Lime fines dust, FES dust)</li></ol>	198800	155844		
3. Mill Scale	61764	62026		

# (c) (1). Total Quantity Recycled/Reutilized within the Unit

	Total Quantity Recycled/Reutilized within th Unit (MT)			
Name of the Waste	During the previous Financial Year (2021-22)	During the current Financial Year (2022-23)		
1. Char	68512	100838		
2. SMS Slag	470180	469536		
3. BF Slag	Nil	24		
4. APC Dust (ESP, Bag filter Dust, DRI ESP dust, Lime fines dust, FES dust)	86038	29694		
5. Mill Scale	65701	60830		

# (c) (2). Total Quantity Sold

	Total Quantity Sold (MT)				
Name of the Waste	During the previous Financial Year (2021-22)	During the current Financial Year (2022-23)			
1. Char*	163600	79792			
2. SMS Slag**	396316	451662			
3. BF Slag***	1611678	1921678			
4. APC Dust (ESP, Bag filter Dust, DRI ESP dust, Lime fines dust, FES dust)	87958	101788			

<sup>\* 17647</sup> MT Char utilized/ sold from legacy stock. \*\*50002 MT SMS Slag utilized/ sold from legacy stock. \*\*\* 99894 MT BF Slag sold from legacy stock.

## (c) (3). Total Quantity Disposed/Stored

Name of the Waste	Total Quantity (MT)			
	2021-22	2022-23		
SMS Slag (Stored inside the plant)	15768	Nil		
2. BF Slag (Stored inside the plant)	143187	26064		
3. APC Dust (ESP, Bag filter Dust, DRI ESP dust, Lime fines dust, FES dust) (Stored inside the plant)	24804	24363		
4. Mill Scale (Stored inside the plant)	Nil	1196		
5. Fly Ash & Bottom Ash (Utilised externally)	385836	356629		
6. Fly Ash (Stored inside the plant)	Nil	1792		

Fly ash and Bottom Ash generated during 2022-23 were used outside the plant for NH construction, bricks making and reclamation of abandoned stone quarries.

PART - F

Chemical Composition of majority of waste as produced in process of Tata Steel, Meramandali operation is given below:

Name of the Wastes	Che	mical C	omposi	tion (%)	Disposal Method
ETP-Sludge	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 39.2 : 23.3; : 10.3 :0.36 :0.049 :0.78 :1.21	2 K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> S <b>0</b> <sub>3</sub>	:1.65	Steel Making Process
ETP Sludge From CRM	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 2.40 : 1.15 : 3.72 : 0.03 : 0.10 :21.81 : 2.54	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	: 1.22 : 0.52 : 0.45 : 0.17 : 17.5 : 1.13 : 42.75	Stored in special containers followed by disposal at CHWTSDF.
BOD plant Sludge	Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO Na <sub>2</sub> O	: 0.08 : 7.28 : 0.36 : 0.064 : 0.16 :0.02 : 0.24	K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> CI LOI	: 0.65 : 0.06 : 0.45 : 0.23 : 80.2	Recycle in Coke Oven with in plant permises
Decanter Tar Sludge	MgO	: 0.04 : 0.01 : 0.94 : 0.001 : 0.015 :0.003 : 0.005	K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> CI LOI	: 0.026 : 0.16 : 0.07 : 0.29 : 66.4	Recycle in Coke Oven with in plant permises
Alkali Residue	Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 0.84 : 49.97 : 0.21 : 0.374 : 1.87 :1.13 : 0.38	K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> CI LOI	: 0.42 : 0.001 : 0.85 : 0.16 : 43.2	Stored in designated containers followed by disposal at CHWTSDF.
Flue Dust	Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub>	: 4.18 : 1.79 : 57.7 : 0.09 0.056	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C	:1.13 :1.37 :0.001 :1.78 :10.24	Reused in Sinter Plant with in plant permises

	CaO MgO	:2.28 :0.74	CI LOI	: 0.13 :11.4	
BOF GCP Sludge (LD Sludge)	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 4.32 : 1.78 : 53.1 :0.12 :0.095 :12.45 :4.02	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	:1.16 :0.97 :0.001 :0.31 :0.85 :0.075 :2.75	Reused in Sinter Plant with in plant permises
SMS Slag	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 13.42 : 1.78 : 26.7 :0.84 :0.022 :45.22 :10.80	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	:1.58 :0.88 :0.20 :0.20 :0.07 : 0.27 :0.52	Processed in MRP for separation of Mag and Non-Mag. Magnetic material recycled in steel making process. Non-Mag being used in sinter, brick manufacturing, & road making.
Lime Fine De-dusting Dust	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 2.41 : 1.12 : 2.68 :0.10 :0.066 :45.63 :12.8	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	:3.01 :0.89 :0.03 :0.26 :5.01 : 0.58 :23.15	Reused in Sinter Plant with in plant permises
Mill Scale	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 0.09 : 0.32 : 65.4 :0.01 :0.012 :0.20 :0.99	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	:1.33 :0.74 :0.001 :0.03 :0.13 : 0.05 :2.47	Reused in Sinter Plant with in plant permises
GCP Dust	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 14.65 : 1.94 : 29.3 :0.15 :0.049 :3.44 :1.45	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	:1.33 :0.87 :0.001 : 1.46 : 30.7 : 0.45 : 35.71	Reused in Sinter Plant with in plant permises
BF Granulated Slag	SiO <sub>2</sub> Al <sub>2</sub> O <sub>3</sub> Fe(T) TiO <sub>2</sub> MnO CaO MgO	: 32.99 : 15.58 : 1.10 :0.71 :0.065 :31.77 :9.14	Na <sub>2</sub> O K <sub>2</sub> O P <sub>2</sub> O <sub>5</sub> SO <sub>3</sub> C CI LOI	:1.55 :1.34 :0.001 : 1.61 : 0.24 : 0.14 : 0.61	Sold to cement plant

# PART – G

SN	Pollution abatement Measures taken in 2022-23	Impact of pollution control measure on conservation of natural resources and cost of production
1	Water Management	Freshwater consumption in closed circuit has been reduced by increasing the Cycle of Concentration (COC) up to 8.
2	Installation of APCE	Reduction in specific PM emission and to be continued. Installation of high frequency transformer rectifier (HFTR) and micro-pulse at Sinter Plant and HFTR at DRI to reduce stack emission. New DE system (bag filters) were provided in Raw material handling.
3	Green Belt Development	We have planted 19893 nos. saplings during April 2022 to March 2023 both inside and outside the plant.
4	Dust Suppression	05 Nos. of vehicle mounted mist canon cum road washers have been engaged to control fugitive dust.  42.8 KMs of road has been concreted/ paved and 04 Nos. of mechanical road sweeping machines have been engaged for road cleaning.  Dust suppression system has been installed in Wagon Tippler to reduce fugitive dust emission during Wagon tippling along with facilities are also for pre wetting of railway wagons  Spillage reduction in conveyor junction houses by installation of Martin lip double skirt rubber & thereby reducing fugitive emission.  Installed 05 Nos. of wheel washing system at RMHS/RMPP, DRI, WHRB, Blast Furnace Power Plant (I&II).
5	PM10 Analyzer Installed	6 no. of Portable PM10 Analyzer have been installed at strategic location of different unit to assess Ground Level Concentration of PM10.
6	Mechanical covering of Hyvas	Mechanical covering of Fly ash carrying vehicle to avoid overload and spillage of fly ash on road.
7	Installed Fluoride treatment plant at Coke Oven and SMS	Commissioned Fluoride Treatment Plant for treatment of Fluoride in Coke Oven 2 and SMS wastewater.

Cost Estimation of Pollution Control (in Rs. Crores)						
Description Expenditure in crores during 2022-23						
Description	Capital Expenditure	Operational Expenditure				
Air Pollution Control	123	56				
Water Pollution Control	17	31				

Solid Waste Management	0	127
Hazardous Waste Management	0	2.1
Biomedical Waste Management	0	0.03
Green Belt Development	0.07	2.3
Miscellaneous#	0.37	10
Total	140	229

<sup>\*</sup>Miscellaneous extenditure includes Housekeeping, Lab Equipment (Capex), Study, consultancy fee, Statutory Fee, etc.

#### Details of Plantation (nos.) done from April 2022 to March 2023

N/1 = x= 4 l=	Plantation in Numbers		Species
Month	Inside	Outside	Species
April 2022	40	0	Peltophorum, Terminalia cattapa, Pongamia, Kadamba, Pongamia, Neem, Mimousopselangi, Michelia Champak, Samnea samam, Cassia seamea, Jacaranda, Cassia fistula, Momousops elangi, Custard apple, Mango, Jackfruit, Guava, Sapota
May 2022	0	0	
June 2022	643	0	
July 2022	5915	0	
August 2022	12810	10	
September 2022	60	0	
October 2022	100	0	
November 2022	115	0	
December 2022	200	0	
January 2023	0	0	
February 2023	0	0	
March 2023	0	0	
Total	19883	10	

PART – H

Additional measures/investment proposals for environmental protection including abatement of pollution, and prevention of pollution.

- Upgradation of the existing pollution control equipment to minimize the levels of particulate matter (PM) emissions.
- Improvement in water recycling facility for reducing the specific water consumption.
- New pollution control equipment is with more stringent design emission value.
- Installation of decanter to recover water from sludge of primary treatment plant.
- Installation of wind screen along the boundary line at RMHS is in progress.
- Installation of 7 Nos. of HD IP Camera is in progress.

#### PART - I

#### Any other undertaken project for improving the quality of environment

- Boiler of Captive power plants have been converted from coal fired to gas fired, thus there is reduction in generation of fly ash in the power plant.
- LD slag after metal recovery is being used internally in the manufacturing process as well as externally in brick and road making works. Slag Atomisation Plant is under commissioning.
- Zero effluent discharge (ZED) installation is in advance stage and will be completed by FY 24.
- Energy efficiency improvement in operations of TSM works by installing variable Frequency Drive and Back Pressure Turbo Generator.
- Installation of high frequency transformer rectifier (HFTR) at DRI to reduce stack emission.
- Installation of industrial vacuum cleaner (IVC) at Junction houses and material transfer point.