

TSL/SPCB/TS-03/2025-19/593 September 25, 2025

The Member Secretary
State Pollution Control Board, Odisha
Parivesh Bhawan, A/118,
Nilakantha Nagar, Unit-VIII,
Bhubaneswar-751 012

Subject: Submission of Environment Statement report for Financial Year 2024 - 2025 for Tata Steel Limited, Meramandali - Regarding.

Reference: Board's Consent Order no. 5823/IND-I-CON-5440, dated 24.03.2025.

Dear Madam,

This has reference to the captioned subject and letter cited above. Please find enclosed herewith dully filled "Environment Statement report (Form-V)" for the Financial Year 2024-2025 in prescribed format for 5.6 MTPA crude steel production at Tata Steel Limited, Meramandali, Dhenkanal, Odisha for your kind perusal.

This is in line with the compliance to the statutory requirement.

Thanking you

Yours faithfully,

For Tata Steel Limited

Anoop Srivastava

Chief Environment - TSM

Anoop soivatava

Encl: As above

Copy to:

1. The Regional Officer, State Pollution Control Board, Odisha, Angul.

2. Deputy Director General of Forests (C), Ministry of Environment, Forest and Climate Change, Regional Office, A/3, Chandshekharpur, Bhubaneswar – 751023.

TATA STEEL LIMITED

Narendrapur Kusupanga Meramandali Dhenkanal 759 121 Registered Office Bombay House 24 Homi Mody Street Fort Mumbai 400 00 Corporate Identity Number L27100MH1907PLC000260 ndia Tel 91 6762 352000 91 22 66654282 Lax 94 02 60657724 www.tatataccl.oop

[FORM-V] (see rule 14) Environment Statement for the financial year ending 31st March 2025 for Tata Steel Limited, Meramandali

PART – A

1.	Name & Address of the owner/occupier of the industry, operation or process	Sri Thachat Viswanath Narendran, CEO & MD Tata Steel Limited At: Narendrapur, PO: Kusupanga Via: Meramandali, Dist.: Dhenkanal, Pin: 759121, Odisha
2.	Industry Category	Red-A
	Primary (STC Code),	Large Metallurgical Industry
	Secondary (STC Code)	Integrated Iron & Steel Industry
3.	Production capacity-Units	 Production Capacity: 5.6 MTPA Crude Steel. Production During 2024-25: 5.19 Million Tons Crude Steel. (Major units are: RMHS & RMPP, Sinter Plants, DRI, Coke Ovens, Blast Furnaces, Lime Plant, SMS, BOF, HSM, CRM, Captive Power Plant, Industrial By-Product Management Division and Utilities including Air Sepretaion Units.)
4.	Year of establishment	2006
5.	Date of last environment statement submitted	13 th September, 2024 vide letter no.TSL/SPCB/TS-03/2024-15/489

PART – B

I) Water Consumption (m³/day)

Water Consumption	During the previous Financial Year (2023-24)	During the current Financial Year (2024-25)
Industrial Consumption (Inside Works as Makeup water)	51,029	52,993
Domestic Consumption (Inside Works as Drinking water)	3,773	4,054

Name of the Products	Fresh water consumption/ unit of products (m³/tcs)						
	During the previous During the current						
	Financial Year (2023-24)	Financial Year (2024-25)					
Crude Steel (Slab/ Billet)	3.36	3.41					

II) Raw Material Consumption (Works):

	Name of	Consumption of raw material per unit of output (MT/tcs)			
Name of Raw materials	Name of Products	During the previous Financial Year (2023-24)	During the current Financial Year (2024-25)		
Iron Ore (Lump &Fine)		1.26	1.22		
Purchase Pellet		0.33	0.36		
Limestone & Dolomite		0.37	0.35		
Quartz		0.03	0.03		
Coking Coal		0.67	0.67		
Non-Coking coal		0.35	0.30		
Scrap	Crude Steel (Slab/Billet)	0.07	0.06		
Ferro-Chromium	(Glab/Billet)	0.0003	0.0002		
Ferro-Manganese		0.0029	0.0027		
Ferro-Silicon		0.0002	0.0001		
Silico-Manganese		0.0011	0.0011		
Zinc		0.0007	0.0007		
Zinc Alloy (Premix)		0.0008	0.0012		

PART – C

Pollution generated
(Parameters as specified in the Consent issued)

Pollutants	Quantity of pollutants discharged to Lingra Nallah (mass/day)		pollutants d Lingra	Concentrations of pollutants discharged to Lingra Nallah (mass/volume)			
	(Tons	s/day)	(m ₂	g/l)	%		
(a) Water	2023-24	2024-25	2023-24	2024-25	2024-25		
TSS	0.188	0.238	90.17	51.83	(-) 48.17 %		
COD	0.080	0.101	38.26	32.67	(-) 86.93 %		
Ammonia as N	0.046	0.006	2.24	0.1	(-) 99.80 %		
BOD	0.089	0.011	4.28	3.78	(-) 87.40 %		
Phenols	< 0.0015	< 0.0013	BDL (< 0.5)	BDL (< 0.5)	(-) 50 %		
Total Cyanide (as CN ⁻)	< 0.0003	< 0.0003	BDL (< 0.1)	BDL (< 0.1)	(-) 50%		

Note: BDL: Below detection limit, Detection Limit for Phenols and Cyanide is 0.5 and 0.1 respectively.

Pollutants		Quantity of pollutants discharged (mass/day)		Concentrations of pollutants (mass/volume)		
(b)Air	2023-24	2024-25	2023-24	2024-25	2024-25	
(emissions)	Tons	s/day	mg/	%		
PM	6.59	6.50	14.33	13.51	(-) 72.98 %	
SO2	50.52	49.73	418.93	427.26	(-) 28.79 %	
NOx	24	20.85	143.72 130.88		(-) 70.92 %	

1. Surface Water Quality (2024-2025)

Parameter	Unit	Kisind	a Nalla	Lingra Nalla		
Parameter	Ollit	U/S	D/S	U/S	D/S	
pH Value	ı	6.92 – 8.58	7.32 – 8.35	6.78 - 8.50	7.36 - 8.56	
Colour	Haze n	BDL (DL:1.0)	BDL (DL:1.0)	BDL (DL:1.0)	BDL (DL:1.0)	
Temperature	°C	25 – 25.3	25 – 25.2	25 – 25.2	25 – 25.2	
Total Suspended Solids	mg/l	3.8 - 31.2	2.6- 28.3	3.2-14	4.1-18.2	
Ammoniacal Nitrogen	mg/l	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	
Arsenic as As	mg/l	BDL(DL:0.005)	BDL(DL:0.005)	BDL(DL:0.005)	BDL(DL:0.005)	
BOD, 3days at 27°C	mg/l	2.1-5.6	2.0-5.6	2.6-5.3	3.2-6.4	
Boron as B	mg/l	BDL (DL:0.25)	BDL (DL:0.25)	BDL (DL:0.25)	BDL (DL:0.25)	
Cadmium as Cd	mg/l	BDL (DL:0.001)	BDL (DL:0.001)	BDL(DL:0.001)	BDL(DL:0.001)	
Calcium as Ca	mg/l	18.1-80.8	16.5-80.8	13-89.0	16.8-64.4	
Chlorides as Cl	mg/l	8.6-158.4	9.7-148.5	11.1-152	13.2-126	
COD	mg/l	9.6 – 28.0	12.0 – 23.0	3.4 - 20	7.8 - 28	
Copper (as Cu)	mg/l	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	
Cyanide as CN	mg/l	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	
Fluoride as F-	mg/l	0.22 - 4.2	0.21 – 6	0.13 - 1.2	0.17 - 2.6	
Free Ammonia	mg/l	BDL(DL:0.1)	BDL(DL:0.1)	BDL(DL:0.1)	BDL(DL:0.1)	
Hexa Chromium (Cr+6)	mg/l	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	
Iron as Fe	mg/l	0.96 - 5.4	0.14-4.9	0.18 – 2.0	0.16-1.0	
Lead (as Pb)	mg/l	BDL (DL:0.005)	BDL (DL:0.005)	BDL(DL:0.005)	BDL(DL:0.005)	
Manganese (as Mn)	mg/l	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	
Mercury (as Hg)	mg/l	BDL(DL:0.0002)	BDL(DL:0.0002)	BDL(DL:0.0002)	BDL(DL:0.0002)	
Nickel (as Ni)	mg/l	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	BDL (DL:0.01)	
Nitrate as N	mg/l	0.36 - 0.86	0.16 – 1.14	0.60 - 1.89	0.11 – 3.89	
O&G	mg/l	BDL (DL:1.4)	BDL (DL:1.4)	BDL (DL:1.4)	BDL (DL:1.4)	
Phenolic Compound	mg/l	BDL (DL:0.001)	BDL (DL:0.001)	BDL (DL:0.001)	BDL (DL:0.001)	
Phosphate as P	mg/l	0.11 - 0.85	0.07 - 0.84	0.10 - 0.29	0.10 to 0.40	
Residual Free Chlorine (RFC)	mg/l	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	
Selenium (as Se)	mg/l	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)	BDL (DL:0.005)	
Sulphide (as S) mg/l	mg/l	BDL (DL:0.05)	BDL (DL:0.05)	BDL (DL:0.05)	BDL (DL:0.05)	
Total Kjheldal Nitrogen (TKN)	mg/l	BDL (DL:0.3)	BDL (DL:0.3)	BDL (DL:0.3)	BDL (DL:0.3)	
Total Chromium (as Cr)	mg/l	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	
Total Nitrogen Content	mg/l	0.51-2.02	0.68 – 1.55	0.74 - 2.08	0.60 - 4.68	
Vanadium (as V)	mg/l	BDL(DL:0.05)	BDL(DL:0.05)	BDL(DL:0.05)	BDL(DL:0.05)	
Zinc (as Zn)	mg/l	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	BDL (DL:0.02)	

NB: U/S: Upstream; D/S: Downstream; BDL: Below Detection Limit; DL: Detection Limit

2. ETP Treated Effluent Quality (2024-2025)

Parameter	UOM	BOD-	1Treated e	effluent	BOD-2 Treated effluent		
Parameter	UCIVI	Min	Max	Avg	Min	Max	Avg
pН	-	6.8	7.6	7.2	6.65	7.2	6.9
Total Suspended Solid	mg/l	28	80	54	22	48	35
Oil & Grease	mg/l	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)
Chemical Oxygen Demand (COD)	mg/l	120	230	175	110	180	145
Biochemical Oxygen Demand (BOD)(27°C for 3 days)	mg/l	16.5	29	22.5	15.8	27	21.3
Total Cyanide (as CN ⁻)	mg/l	0.12	0.2	0.16	0.11	0.14	0.12
Phenol	mg/l	0.48	0.87	0.67	0.57	0.81	0.69

Parameter	UOM		ETP-1			ETP-2	
Parameter	OOW	Min	Max	Avg	Min	Max	Avg
рН	-	6.93	8.15	7.54	6.53	7.88	7.20
Total Suspended Solid	mg/l	13	37	25	18	35	26.5
Chemical Oxygen Demand (COD)	mg/l	19	45	32	18	34	26
Biochemical Oxygen Demand (BOD) (27°C for 3 days)	mg/l	3.5	7	5.25	3.3	5.4	4.35
Iron as Fe	mg/l	0.27	0.72	0.49	0.1	0.6	0.35
Oil & Grease	mg/l	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)

Parameter	UOM		ETP-3		CRM ETP			
Parameter	OOM	Min	Max	Avg	Min	Max	Avg	
pН	-	6.76	8.3	7.53	6.76	8.13	7.44	
Total Suspended Solid	mg/l	19	41	30	18	87	52.5	
Chemical Oxygen Demand (COD)	mg/l	29	37	33	100	180	140	
Biochemical Oxygen Demand (BOD) (27°C for 3 days)	mg/l	3.7	5.4	4.55	14.6	26.2	20.4	
Iron as Fe	mg/l	0.29	0.89	0.59	0.79	2.8	1.79	
Oil & Grease	mg/l	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	

3. Sewage Treatment Plant -Treated outlet quality (2024-2025)

Parameter	ПОМ	BF-1 STP			,	SMS-1 STF)
	UOM	Min	Max	Avg	Min	Max	Avg
рН	-	6.91	7.85	7.38	6.51	7.81	7.16
TSS	mg/l	18	47	32.50	18	42	30
BOD	mg/l	7.8	41	24.40	8.7	44	26.35

4. Water Discharge Quality (2024-2025)

Parameter	UOM	Discharg	ge to Ling	ra Nallah	Discharge to Kisinda Nallah			
Parameter	UCIVI	Min	Max	Avg	Min	Max	Avg	
рН	-	7.42	8.43	8.10	7.34	8.34	7.84	
Total Suspended Solid	mg/l	21	247	51.83	33	61	44.67	
Oil & Grease	mg/l	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	BDL (DL:5.0)	
Chemical Oxygen Demand (COD)	mg/l	22	66	32.67	28	39	34.92	
Biochemical Oxygen Demand (BOD)(27°C for 3 days)	mg/l	2.80	4.50	3.78	3.20	5.20	3.97	
Total Cyanide	mg/l	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	
Ammonical Nitrogen	mg/l	BDL (DL:0.1)	BDL (DL:0.1)	BDL (DL:0.1)	0.10	4.10	1.08	

5. Ambient Air Quality (2024-2025) – Monitored at CAAQMS

Devemeters HeM	LIOM Nove	C	CAAQMS-1		CAAQMS-2			CAAQMS-3			
Parameters	UoM	Norm	Min	Max	Avg	Min	Max	Avg	Min	Max	Avg
PM10	μg/m³	100	39.7	184	114	69.6	243	162	105	193	153
PM2.5	μg/m³	60	13.3	67.9	39.6	26.5	113	63.4	35.4	96.9	57.4
SO ₂	μg/m³	80	10.9	39.6	16.3	21.5	23.4	22.7	2.1	10.1	5.1
NO ₂	μg/m³	80	6.2	24.9	18.1	4.6	12.4	9.7	16.1	19.3	18.0
СО	mg/m³	2	0.4	8.0	0.6	0.43	0.9	0.7	0.7	1.2	0.9

Darametera	LIOM Norm			CAAQMS-4	1	CAAQMS-5				
Parameters	UoM	OOW	UOW	Norm	Min	Max	Avg	Min	Max	Avg
PM10	μg/m³	100	41.5	188	109	64.2	242	139		
PM2.5	μg/m³	60	14.8	92.0	52.7	22.3	103	55.8		
SO ₂	μg/m³	80	5.2	8.1	6.1	8.1	18.7	13.1		
NO ₂	μg/m³	80	7.2	33.5	18.5	7.3	26.8	14.0		
CO	mg/m³	2	0.2	0.6	0.3	0.2	0.9	0.5		

Doromotoro	LIGM	Morm	C	AAQMS-6		CAAQMS-7		
Parameters	UoM	Norm	Min	Max	Avg	Min	Max	Avg
PM10	μg/m³	100	85.0	187	132	79.1	246	143
PM2.5	μg/m³	60	32.3	63.7	45.0	30.4	126	64.1
SO ₂	μg/m³	80	8.7	19.6	14.1	8.1	50.6	32.0
NO ₂	μg/m³	80	14.7	26.5	20.8	14.6	22.4	17.1
CO	mg/m³	2	0.4	1.0	0.7	0.7	1.1	0.8

<u>NB</u>. CAAQMS-1: Near Township; CAAQMS-2: Near AEL Boundary; CAAQMS-3: Near CRM; CAAQMS-4: Near Water Complex; CAAQMS-5: Near Coke Oven 2; CAAQMS-6: Near Wagon Tippler; CAAQMS-7: Near Material Gate.

Values are derived from 24 hourly average data except CO values which are derived from 8 hourly average data.

6. Ambient Air Quality (2024-2025) - Manual Monitoring Report

Parameters	UoM		CAAQMS-1			CAAQMS-2	
		Min	Max	Avg	Min	Max	Avg
Ammonia (NH3)	μg/m³	21.6	53.4	29.6	21.0	46.0	27.5
Arsenic as (As)	μg/m³		BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)
Benzene	μg/m³	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)
Benzo(a)Pyrene	μg/m³	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)
Carbon	μg/m³	0.2	0.6	0.5	0.3	8.0	0.6
monoxide (CO)							
Lead (as Pb)	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nickel as Ni	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nitrogen Dioxide	μg/m³	22.8	45.8	29.7	25.9	45.1	31.1
as (NO2)							
Ozone (as O3)	μg/m³	20.4	33.9	24.2	22.8	29.3	26.8
PM ₁₀ (Particulate	μg/m³	67.1	95.8	74.3	76.5	97.3	85.8
Matter<10 µm)							
PM _{2.5} (Particulate	μg/m³	32.8	51.3	37.6	42.5	57.2	46.9
Matter < 2.5 μm)							
Sulphur Dioxide	μg/m³	6.2	9.2	7.0	6.4	11.0	7.6
as (SO2)							

Parameters	UoM		CAAQMS-3			CAAQMS-4	
		Min	Max	Avg	Min	Max	Avg
Ammonia (NH3)	μg/m³	17.6	55.6	24.9	30.1	48.7	35.1
Arsenic as (As)	μg/m³	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)
Benzene	μg/m³	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)
Benzo(a)Pyrene	μg/m³	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)
Carbon monoxide	µg/m³	0.3	1.0	0.6	0.2	0.8	0.5
(CO)							
Lead (as Pb)	μg/m³	0.6	0.1	0.6	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nickel as Ni	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nitrogen Dioxide	μg/m³	23.4	48.8	27.6	22.0	40.3	27.3
as (NO2)							
Ozone (as O3)	μg/m³	21.4	30.2	22.2	24.8	30.6	27.2
PM ₁₀ (Particulate	μg/m³	76.9	98.7	82.5	70.8	92.9	77.3
Matter<10 µm)							
PM _{2.5} (Particulate	μg/m³	37.2	54.7	42.0	34.6	48.1	39.9
Matter < 2.5 µm)							
Sulphur Dioxide	μg/m³	6.9	9.4	7.8	6.7	7.8	7.3
as (SO2)							

Parameters	UoM		CAAQMS-5			CAAQMS-6	
		Min	Max	Avg	Min	Max	Avg
Ammonia (NH3)	μg/m³	31.9	57.6	36.3	27.6	47.3	32.0
Arsenic as (As)	μg/m³	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)
Benzene	μg/m³	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)
Benzo(a)Pyrene	μg/m³	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)
Carbon monoxide	μg/m³	0.3	1.0	0.8	0.4	8.0	0.6
(CO)							
Lead (as Pb)	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nickel as Ni	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nitrogen Dioxide	μg/m³	23.1	42.3	39.5	30.2	42.1	35.7
as (NO2)							
Ozone (as O3)	μg/m³	23.6	30.4	26.7	24.5	38.8	29.0
PM10(Particulate	μg/m³	82.6	96.7	88.9	72.5	95.6	87.0
Matter<10 µm)							
PM2.5	μg/m³	45.2	57.0	49.5	36.3	52.1	45.8
(Particulate							
Matter < 2.5 μm)							
Sulphur Dioxide	μg/m³	7.8	9.1	8.5	6.9	9.3	8.3
as (SO2)							

Parameters	UoM		CAAQMS-7	
		Min	Max	Avg
Ammonia (as NH3)	μg/m³	18.3	57.6	28.1
Arsenic as (As)	μg/m³	BDL(DL:1.0)	BDL(DL:1.0)	BDL(DL:1.0)
Benzene	μg/m³	BDL(DL:4.2)	BDL(DL:4.2)	BDL(DL:4.2)
Benzo(a)Pyrene	μg/m³	BDL(DL:0.5)	BDL(DL:0.5)	BDL(DL:0.5)
Carbon monoxide (as CO)	μg/m³	0.4	1.0	0.8
Lead (as Pb)	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nickel as Ni	μg/m³	BDL(DL:0.01)	BDL(DL:0.01)	BDL(DL:0.01)
Nitrogen Dioxide as (NO2)	μg/m³	24.6	42.3	31.3
Ozone (as O3)	μg/m³	21.6	30.4	25.6
PM10(Particulate Matter<10 µm)	μg/m³	72.6	96.7	82.6
PM2.5 (Particulate Matter < 2.5 μm)	μg/m³	33.9	57.0	43.3
Sulphur Dioxide as (SO2)	μg/m³	6.6	9.1	7.7

PART – D

(As specified under The Hazardous and Other Wastes (Management & Transboundary Movement Rules, 2016)						
	Total Qua	ntity (MT)				
Hazardous waste	During the previous Financial Year (2023-24)	During the current Financial Year (2024-25)				
(a) From Process						
Used/ Spent Oil	276.83	270				
Waste residue containing oil	200.2	220				
Oily Sludge	390.3	330				
Rejected Chemical Container	Nil	560				
Insulation Material	97.58	200				
Alkali Residue	15	10				
Zinc Ash & Zinc Dross	394.55	376				
Spent Solvent (Waste Thinner - Oily Waste)	90.76	38				
Waste Copper	-	20				
Used Lead acid battery including grid plates and other lead scrap/ashes/residues/Lead Pot	-	98				
(b) From Pollution Control Facilities						
BOD plant Sludge (Coke Oven By-Product Plant Residue)	3739.68	4052				
Decanter Tar Sludge (Coal Tar Sludge)	1860	2526				
ETP Sludge/Chemical Sludge from wastewater treatment plant	673.84	1230				
Air Pollution Control Device dust/residue (Flue dust, Gas Cleaning Plant Sludge, LD Sludge, Air Pollution Control Device dust/residue)	237697.76	227790				

PART – E

Solid Wastes

Total Quantity Generated

	Total Quantity G	Generated (MT)	
Name of the Waste	During the previous Financial Year (2023-24)	During the current Financial Year (2024-25)	
(a) From Process			
1. Char (DRI)	163377	150996	
BF Slag (Granulated Slag + Air Cooled Slag)	1892405	1815360	
3. SMS Slag (LD)	989074	984092	
4. Bottom Ash	27567	16985	
Other Waste of DRI (Wet Scrapper Dust +Acreation Material +Cold ESP+Cooler Oversize)	-	148685	
(b) From Pollution Control Facilities			
1. Fly Ash	419397	374884	
2. Mill Scale	73430	71103	
3. WHRB Ash	-	279702	

(C-1). Quantity Recycled or Reutilised (Internal Utilisation)

	Total Quantity (MT)				
Name of the Waste	During the previous Financial Year (2023-24)	During the current Financial Year (2024-25)			
1. Char (DRI)	80756	91264			
BF Slag (Granulated Slag + Air Cooled Slag)	0	56761			
3. SMS Slag (LD)	2441562*	257257			
4. Mill Scale	92212	94807			
5. Other Waste of DRI (Wet Scrapper Dust +Acreation Material +Cold ESP+Cooler Oversize)	-	51158			

(C-2). Quantity Recycled or Reutilised (External Utilisation) (MT)

	Total Q	uantity (MT)
Name of the Waste	During the previous Financial Year (2023-24)	During the current Financial Year (2024-25)
1. Char (DRI)	82563	89849
BF Slag (Granulated Slag + Air Cooled Slag)	1907127	1830391
3. SMS Slag (LD)	3090*	2237770#
4. Other Waste of DRI (Wet Scrapper Dust +Acreation Material +Cold ESP+Cooler Oversize)	-	85671
5. Fly Ash & Bottom Ash (Sent to Cement Plant, Road Making, Brick Making, Balance if any sent to filling of low lying area)	446964	391869
Ash generated from Waste Heat Recovery Boilers of DRI (WHRB)	-	279702

Note:

*FY 2023-24: The total quantity of SMS slag was 2,441,562 MT for Financial Year 2023-24 comprises of external utilisation (2,068,827 MT) and internal utilisation (372,736 MT). Please note that figure submitted in the previous environment statement of FY 2023-24 was inadvertently and erroneously noted as 3,090 MT SMS slag which was reported under external utilisation.

#FY 2024-25: The quantities of SMS Slag given in the external utilisation includes legacy stock, embedded pre 2018. There may be still legacy stock available within the premises which shall be subsequently utilised as per the CPCB guidelines.

PART – F

Chemical Composition of majority of waste as produced in process of Tata Steel
Limited, Meramandali operation is given below:

Limited, Meramandali operation is given below:							
Name of the Wastes	Che	mical Cor	npositio	n (%)	Disposal Method		
ETP-Sludge	SiO ₂	: 39.21	Na₂O	:0.41	Reuse within Plant		
	Al_2O_3	: 23.32	K_2O	:1.65			
	Fe(T)	: 10.3	P_2O_5	:0.06			
	TiO ₂	:0.36	$S0_3$:0.28			
	MnO	:0.049	С	:3.51			
	CaO	:0.78	CI	:0.23			
	MgO	:1.21	LOI	:16.28			
ETP Sludge From CRM	SiO ₂	: 2.40	Na₂O	: 1.22	Stored in special		
	Al_2O_3	: 1.15	K_2O	: 0.52	containers followed by		
	Fe(T)	: 3.72	P_2O_5	: 0.45	disposal at CHWTSDF/ Reuse within Plant		
	TiO_2	: 0.03	$S0_3$: 0.17	Reuse within Flant		
	MnO	: 0.10	С	: 17.5			
	CaO	:21.81	CI	: 1.13			
	MgO	: 2.54	LOI	: 42.75			
BOD plant Sludge	Al_2O_3	: 0.08	K_2O	: 0.65	Mixed with coal and used		
	Fe(T)	: 7.28	P_2O_5	: 0.06	in Coke making process		
	TiO_2	: 0.36	$S0_3$: 0.45			
	MnO	: 0.064	CI	: 0.23			
	CaO	: 0.16	LOI	: 80.2			
	MgO	:0.02					
	Na ₂ O	: 0.24					
Decanter Tar Sludge	Al_2O_3	: 0.04	K_2O	: 0.026	Mixed with coal and used		
	Fe(T)	: 0.01	P_2O_5	: 0.16	in Coke making process		
	TiO ₂	: 0.94	S0₃	: 0.07			
	MnO	: 0.001	CI	: 0.29			
	CaO	: 0.015	LOI	: 66.4			
	MgO	:0.003					
All 1155 11	Na ₂ O	: 0.005	14.0	0.40			
Alkali Residue	Al_2O_3	: 0.84	K_2O	: 0.42	Stored in designated		
	Fe(T)	: 49.97	P_2O_5	: 0.001	containers followed by disposal at CHWTSDF/		
	TiO ₂	: 0.21	S0₃	: 0.85	Reuse within plant		
	MnO	: 0.374	CI	: 0.16	Trouble William Plant		
	CaO	: 1.87	LOI	: 43.2			
	MgO	:1.13					
FI D (Na ₂ O	: 0.38	N 0	4.40			
Flue Dust	SiO ₂	: 4.18	Na₂O	:1.13	Reused in Sinter Plant		
	Al_2O_3	: 1.79	K ₂ O	:1.37	with in plant permises		
	Fe(T)	: 57.7	P_2O_5	:0.001			
	TiO ₂	:0.09	S0₃	:1.78			
	MnO	:0.056	С	:10.24			

	CaO MgO	:2.28 :0.74	CI LOI	: 0.13 :11.4	
BOF GCP Sludge (LD	SiO ₂	: 4.32	Na₂O	:1.16	Reused in Sinter Plant
Sludge)	Al ₂ O ₃ Fe(T) TiO ₂ MnO CaO MgO	: 1.78 : 53.1 :0.12 :0.095 :12.45 :4.02	K_2O P_2O_5 SO_3 C CI LOI	:0.97 :0.001 :0.31 :0.85 :0.075 :2.75	with in plant premises/Sold to authorized recyclers
SMS Slag	SiO ₂	: 13.42	Na₂O	:1.58	After recovery of metal in
	Al ₂ O ₃ Fe(T) TiO ₂ MnO CaO MgO	: 1.78 : 26.7 :0.84 :0.022 :45.22 :10.80	K ₂ O P ₂ O ₅ SO ₃ C CI LOI	:0.88 :0.20 :0.20 :0.07 : 0.27 :0.52	metal recovery plant, metallic part is used in SMS/sold to recycler. Non metallic portion is used externally/internally in: i) Sinter Making ii) Brick Making iii) Road Making iv) Utilized in low lying area/hardstanding
Mill Scale	SiO ₂	: 0.09	Na₂O	:1.33	Reused in Sinter Plant
	Al ₂ O ₃ Fe(T) TiO ₂ MnO CaO MgO	: 0.32 : 65.4 :0.01 :0.012 :0.20 :0.99	K_2O P_2O_5 SO_3 C CI LOI	:0.74 :0.001 :0.03 :0.13 : 0.05 :2.47	with in plant permises
BF GCP Sludge	SiO ₂	: 14.65	Na₂O	:1.33	Reused in Sinter Plant
	Al ₂ O ₃ Fe(T) TiO ₂ MnO CaO MgO	: 1.94 : 29.3 :0.15 :0.049 :3.44 :1.45	K_2O P_2O_5 SO_3 C CI LOI	:0.87 :0.001 : 1.46 : 30.7 : 0.45 : 35.71	with in plant premises/Sold to authorized recyclers
BF Slag (Granulated	SiO ₂	: 32.99	Na₂O	:1.55	Sold to cement Plant.
Slag + Air Cooled Slag)	Al ₂ O ₃ Fe(T) TiO ₂ MnO CaO MgO	: 15.58 : 1.10 :0.71 :0.065 :31.77 :9.14	K_2O P_2O_5 SO_3 C CI LOI	:1.34 :0.001 : 1.61 : 0.24 : 0.14 : 0.61	Used in Construction

PART – G

S.N	Pollution abatement Measures taken in 2024-25	Impact of pollution control measure on conservation of natural resources and consequently on the cost of production
1	 Central Effluent Treatment Plant commissioned and operated. Blast Furnace Slag granulation unit condensate water recovery and reuse. Rainwater harvesting structures constructed for use of water in different applications. Cycle of Concentration (CoC) maintained more than 5 at Power Systems. 	Reduction of Specific Water consumption
2	 Installation of Air Pollution Control Equipment's Increase of non-coal power generation from 40% to 83% 44% power generation from waste heat recovery Commissioning of 470 KW micro turbine Improvement in BF fuel rate (560 kg/thm to 518 kg/thm) through increase in Pulverised Coal Injection (PCI) rate and agglomerate burden. Improvement of DRI fuel rate from 1256 to 735 kg/tdri 	 Reduction in specific PM emission and to be continued. Reduction in CO2 emission
3	Green Belt Development - 51,873 nos. saplings were planted plant during April 2024 to March 2025.	both inside and outside the

Details of Plantation (nos.) done from April 2024 to March 2025

Month	Plantatio	n in Numbers	Species	
WONTH	Inside	Outside	Species	
April 2024	87	4000		
May 2024	0	20		
June 2024	3831	1520		
July 2024	11774	1470	Deltambarrum Tarmainalia aattama	
August 2024	9400	2600	Peltophorum, Terminalia cattapa, Pongamia, Kadamba, Pongamia, Neem, Mimousopselangi, Michelia	
September 2024	6310	3040		
October 2024	942	2500	Champak, Samnea samam, Cassia	
November 2024	4050	0	seamea, Jacaranda, Cassia fistula,	
December 2024	0	250	Momousops elangi, Custard apple,	
January 2025	24	0	Mango, Jackfruit, Guava, Sapota	
February 2025	0	0		
March 2025	55	0		
Total	36473	15400		

PART – H

Additional investment proposals for environmental protection including abatement of pollution:

- Upgradation of the existing pollution control equipment to minimize the levels of particulate matter (PM) emissions.
- Adaption of best available technology to achieve best in class performance.
- Strive for benchmark status in specific stack dust emissions.
- Improvement in water recycling facility for further reduction in specific fresh water consumption.
- New pollution control equipment with more stringent designed for less emission.
- Rain water harvesting.

The Environment (Protection) Rules, 1896

PART – I (Miscellaneous)

Any other particulars in respect of environment protection and abatment of pollution:

- LD slag after metal recovery, is being used internally in the manufacturing process as well as externally in brick, road making & hardstand works. Slag Atomisation Plant is also in operation.
- Energy efficiency improvement in operations of TSM works by installing variable Frequency Drive and Back Pressure Turbo Generator.
- Installation of industrial vacuum cleaner (IVC) at Junction houses and material transfer point.
- Installation of DE system at junction house 35 & raw material coveying lines.
- COG injection in Blast Furnace & COG injection in DRI. Trial run conducted for Biochar injection in Blast furnaces.
- Reduction of Green House Gas emissions through several decarbonization initiatives.
- Tata Steel Limited, Meramandali is certified by Integared Management System (ISO 14001:2015, ISO 9001:2015 & ISO 45001:2018). IMS audit is being carried out to comply the requirement & management review meeting is being conducted as per ISO requirement to address the concerns of audit and adequate steps taken for continuous environmental improvement.
- Tata Steel Limited Meramandali, is one of the three Integrated Iron & Steel Companies of Tata Steel received ResponsibleSteel™ certification. ResponsibleSteel™ certification is a globally recognized standard aimed at promoting sustainability and responsibility in the steel industry. The audit process involves of various stakeholders, including industry players, civil society, and NGOs, in developing the standards. Specific criteria that companies must meet to be certified, focusing on environmental, social, and governance aspects.
