

The Additional P.C.C.F. (Central)
Eastern Regional Office
Ministry of Environment, Forests & Climate Change
Government of India
A/3, Chandrashekharpur,
Bhubaneswar – 751 023, Odisha

KPO/Env/C-05/ **07** /2019 30.05.2019

Dear Sir,

Sub.: Six monthly Compliance Report for Oct-18 to Mar-19 for Environmental Clearances in respect of 6.0 MTPA Integrated Steel Plant of M/s. Tata Steel at Kalinganagar Industrial Complex, Duburi, Dist. Jajpur, Odisha.

Ref.: EC Granted by MoEF vide Letter No. J-11011/7/2006-IA-II(I) dated 7.11.2006.

: Amendments in EC granted by MoEF vide Letters No. J-11011/7/2006-IA-II (I) dated 10.12.2012 and 13.05.2015

Kindly find enclosed Six Monthly Compliance Report for the period from Oct' 2018 to Mar' 2019 for the conditions stipulated in Environmental Clearance including amendments granted in EC to 6.0 MTPA Integrated Steel Plant of Tata Steel Limited at Duburi, Dist. Jajpur, Odisha for your kind considerations.

We trust the information furnished is in line with your requirement.

Thanking you,

Yours faithfully,

U S Parkhi

Head, Environment, KPO

Encl. a/a

Copy to MS, OSPCB, Bhubaneswar / CPCB Kolkata /OSPCB KNIC

Six Monthly Environment Compliance Report Oct' 2018 to Mar' 2019

For

Integrated Steel Plant Project of Tata Steel

At

Duburi, Dist. Jajpur, Odisha



Environment Department **Tata Steel Limited**Kalinganagar Industrial Complex

Duburi- 755026

Dist Jajpur, Odisha

A Specific Conditions as per EC dated 7.11.2006

i) The gaseous emissions from various process units shall conform to the load/mass based standards notified by this Ministry on 19th May, 1993 and standards prescribed from time to time. The state Boards may specify more stringent standards for the relevant parameters keeping in view the nature of the industry and its size and location. At no time, the emission level shall go beyond the prescribed standards. On-line continuous monitoring system shall be installed in stacks to monitor SPM and interlocking facilities shall be provided so that process can be automatically stopped in case emission level exceeds the limit. Nox burners shall be installed to control NOx levels. VOCs from the coke oven shall be monitored and controlled as per CPCB guidelines. The new standards prescribed by the CPCB for coke oven plants shall be strictly followed.

In-plant control measures for checking ii. fugitive emissions from all the vulnerable sources like coke oven area, Sinter Plant, BF case house, BF stack house, and BOF shop etc. shall be provided. Further, specific measures like water sprinkling and dry fogging (DF) shall be carried out at the stock piles of raw materials, stacker reclaimer, conveyor transfer points and vibrating screens etc. Dust extraction system and bag filter shall be provided for room air cleaning such as sinter plant stock house, BF stock house and BF cast house, BOF shop and Ferro-alloys handling area in steel melting shop etc. Fume extraction system in steel refining units shall also be provided. Centralized de-dusting system i.e. collection of fugitive emissions through suction hood and subsequent treatment through bag filter or any other device and finally emitted through a stack of appropriately designed and height conforming to the standards for induction furnaces in the industry shall be provided. Fugitive emissions shall be controlled, regularly monitored and records maintained.

Status as on 31.03.2019

- All the process units such as Coke Plant, Sinter Plant, Blast Furnace, SMS, and Mill have been designed conforming to the load/mass standards notified by the Ministry to have the gaseous emissions under control and below the prescribed limits.
- Online continuous stack monitoring systems have been installed at stacks of Coke Plant Battery No.1 and 2, Sinter Plant, BF, SMS, LCP and HSM to monitor SPM.
- The units are in operation and emission levels were found within prescribed norms.
- Low NOx burners are installed at CPP (8 Nos for each boilers in all three boilers) and in HSM reheating furnace (84 Nos)
- VOC from coke plant is controlled by On-main charging by HPLA, Hydraulic doors, Door sealing, Door frame cleaner, etc. as per CPCB guidelines and the systems for both the Battery No. 1 as well as Battery -2 are in operations.
- New standards prescribed by CPCB (31.03.2012) for coke ovens are being followed.
- In plant control measures (like Dust extraction systems- DES, Dust Suppression System- DSS and Dry Fog dust suppression systems- DFDSS) are controlling fugitive emissions from the vulnerable sources like coke oven area, Sinter Plant, BF cast house, BF stock house, and BOF shop etc.
- Further specific measures like water sprinkling arrangement at stock piles of raw material handling unit. To control fugitive dusts from conveyor, transfer points and vibrating screens DE, DSS and DFDS are provided at these locations.
- Dust extraction system followed by De-dusting ESP has been provided at Sinter Plant. At Cast house and Stock house of Blast Furnace, separate dust extraction systems followed by ESPs have been provided. In SMS, secondary de-dusting unit (Cyclone separator followed by ESP) has been provided. Fume extraction system in steel refining units has been provided. All the stacks have been designed and installed to meet the requirement of stack heights as per guidelines, for proper dispersion and dilution of pollutants
- In addition to above, following control measures are taken to control of fugitive emissions from other sources are: -
 - Water sprinkling on roads is being done through truck mounted water tankers to suppress road dust due to vehicular movement.
 - o To suppress fine dusts, specially designed vehicle for mist type sprinkling of water

A	Specific Conditions as per EC dated 7.11.2006	Status as on 31.03.2019
		 (through movable High Pressure Mechanized Water jet) has been deployed. Mechanized road sweeping Machines have been deployed for regular road sweeping. Speed limits are enforced for movement of vehicles at the site as per the factory limits Roads (about 23 kms) within the plant site are metaled/ concreted.
iii.	ESP shall be provided to sinter plant and blast furnace. New standards prescribed by the CPCB for coke oven shall be strictly followed. The Company shall install Waste Heat Recovery Boilers (WHRB) to recover the waste heat and generate power from the steam produces by the WHRB. The particulate emissions from the WHRB shall be controlled by installation of ESP as per CPCB specification and particulate emissions shall not exceed 50mg/Nm ³ . Further, the company shall install bag filter, After Burner Chamber (ABC), suction hood, dust extraction device and fume extraction system to control gaseous emissions from the WHRB.	 Higher efficiency ESPs have been provided to Sinter plant, Blast Furnace and SMS. Coke oven plant is designed to comply with new standards prescribed by CPCB for Coke Oven. Waste Heat Recovery Boilers (WHRB) have been installed to recover waste heat which in turn shall be used for in-house power generation from the steam produces by WHRB. Pollution Control Systems have been designed as per CPCB guidelines to control PM emissions below 50 mg/Nm3. Coke Dry Quenching (CDQ) System is provided with bag filters.
iv.	Total requirement of the water from Brahmani /Kharasua river shall not exceed 26.5 MGD. No ground water shall be drawn and used for the plant. The effluent quantity into the industrial drain leading to the Gonda Nalla shall not exceed 92m³/hr and shall conform to the prescribed standards. Ammonia, phenol and cyanide in the effluent should be treated separately and discharged only after meeting the norms prescribed by the OSPCB/CPCB/Ministry under E(P) Act. Cyanide shall meet the standard of 0.2 ppm. TDS in the effluent discharged shall not be more than 2,100 mg/I. The domestic wastewater after treatment in STP shall be used for green belt development.	 Make up water requirement for the plant is < 26.5 MGD. Present water consumption is around 8 MGD. Total effluent discharge envisaged is < 92 m³/hr and it meets the standards prescribed by MoEF/CPCB/OSPCB before discharge into Ganda Nalla. Ammonia, Phenol and Cyanide in the effluent from Coke Oven plant is treated separately in BOD plant of Coke Plant. The BOD plant is in operation. For treatment of domestic wastewater there is a STP. Treated water is utilized for plantation. No groundwater is used for plant operations.
v.	Ground water monitoring around the solid waste disposal site/secured landfill (SLF) shall be carried out regularly and report submitted to the Ministry's Regional Office at Bhubaneswar, CPCB and OPCB.	J Ground water level is monitored and variations are negligible.J Ground water quality is within the permissible limit.

A	Specific Conditions as per EC dated 7.11.2006	Status as on 31.03.2019
vi.	BF slag shall be sold to the cement manufacturers after granulation. Nongranulated BF slag shall be used in road making. BOF slag shall not be dumped anywhere except used for making cement and road etc. proposed in EIA/EMP. Ammonia and tar shall be recovered and remaining solid waste shall be burnt. Gas cleaning plant sludge and mill scales shall be reused in the sinter plant. Char generated shall be used in FBC boiler. The kiln accretions shall be utilized for filling low lying areas. The entire quantity of fly ash generated during the process shall be utilized for making brick. ESP fly ash shall be made available to the cement plants and brick making plants whereas bottom ash shall be disposed off in a suitably designed landfill as per CPCB guidelines to prevent leaching to the sub-soil and underground aquifer.	 JBF slag is sold to cement manufacturers after online slag granulation process (RASA). Majority of BF slag is transported by rail. J Non-granulated BF & BOF slag is used for road making. J In COBPP, Tar and Sulphur is recovered and same is sold as by-product. J Gas cleaning plant sludge and mill scales are utilized in sinter plant. J Mill scale from mills are utilized in sinter plant. J CPP boilers are by-product gas based boilers hence there is no char generation. No fly ash & bottom ash is generated in process.
vii.	The company shall develop surface water harvesting structures to harvest the rain water for utilization in the lean season besides recharging the ground water table.	 Surface run-off during the monsoon is collected and stored in the reservoirs constructed under rain water harvesting schemes. Storm water pond with necessary pumping arrangement to recover storm water in raw water system has been made.
viii.	Green belt shall be developed in at least 33% area within and around the plant premises as per the CPCB guidelines in consultation with DFO.	Green Belt cover is being continuously developed within and around the project site, as well as outside the plant premises (rehabilitation colonies). Cumulative Tree Plantation at TSK Cumulative Tree Plantation at TSK 400000 350000 250000 200000 150000 150000 1000000
ix.	Occupational Health Surveillance of the workers shall be done on a regular basis and records maintained as per the factories Act.	Jinitial & Periodic medical check-up for workers are carried out and records for the same are maintained as per the Factories Act. To strengthen the Occupational Health Surveillance, a system has been made, in which, employee's Gate Pass is issued only after ensuring the initial medical check-up.

A	Specific Conditions as per EC dated 7.11.2006	Status as on 31.03.2019
X.	Recommendations made in the CREP guidelines issued for the steel plants shall be implemented.	 CREP recommendations are being implemented and summarized below: Coke Ovens: Fugitive emissions control system is in place. All the batteries are new one and having coal stamping, charging cum pushing (SCP) machines. SMS: Secondary fume extraction system has been installed. BF: Pulverized Coal injection facilities have been installed. in Blast Furnace, TRT, Tar Free Runners, DE system at Cast House, etc. are also provided. Specific water consumption is less than 8 m³/t of flat product. Online monitoring facilities have been provided. Waste management systems are implemented.
xi.	Rehabilitation and Resettlement plan shall be implemented as per the revised R&R policy and in collaboration with the State Government in a time bound manner and report submitted to the Ministry, it's Regional Office at Bhubaneshwar and OPCB.	Families have been rehabilitated within the framework of "Tata Steel Parivaar" concept as per R & R policy of Odisha Govt. in consultation with the local administration. A dedicated team facilitates the resettlement & rehabilitation effectively.
xii.	The environmental clearance for the mining project and forest clearance for the forest land involved in the mining project shall be obtained from the Ministry prior to operation of the integrated Steel Plant. In case, environmental clearance for the mining proposal from State Govt/Govt. of India is not available, Ministry shall be regularly informed about the source of ore and coal.	 The matter is being pursued with State and Central Government. Coal is being imported. Source of iron ore is mainly from the mines of Tata Steel in Odisha.

В.	General Conditions as per EC dated 7.11.2006	Status as on 31.03.2019
i.	The project authorities must strictly adhere to the stipulations made by the Orissa Pollution Control Board (OPCB) and the State Government	During project execution and subsequent operation phases TSL has strictly adhere to stipulation made by OSPCB and the state Government
ii.	No further expansion or modification in the plant should be carried out without prior approval of the Ministry of Environment and Forests.	Amendments in the Environmental Clearance were granted by MoEF on 10.10.2012 and on 13.05.2015 vide letters no. J-11011/7/2006-IA. II. (I). Our application regarding expansion from 6 MTPA to 8 MTPA has been submitted on 20.09.2016. ToR for expansion was reviewed by EAC Industry-I on 28.10.2016 and granted in March 2017. Draft EIA & EMP Report has prepared.
iii.	At least four ambient air quality-monitoring stations should be established in the downward direction as well as where maximum ground level concentration of SPM, SO ₂ and NOx are anticipated in consultation with the OPCB. Data on ambient air quality and stack emission should be regularly submitted to this Ministry including its Regional Office at Bhopal and the OPCB/CPCB once in six months.	 J Ambient Air quality monitoring Stations are established. J Data on Ambient Air Quality and Stack emissions are submitted regularly on monthly basis to OSPCB and Half yearly basis to MoEF&CC. J Data of Online Continuous Ambient Air quality monitoring stations as well as Continuous Emission Monitoring Systems of Stacks are also being transmitted to the server of OSPCB through Real Time Data Acquisition System (RTDAS). J Remote calibration has been done by CPCB. CPCB has checked remote zero and span check facility installation our CEMS.
iv.	Industrial waste water shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 dated 19 th May, 1993 and 31 st December, 1993 or as amended from time to time. The treated wastewater shall be utilized for plantation purpose.	J For Treatment of Industrial waste water and its recovery & reuse, individual units like Coke Plant, HSM, SMS and BF etc. have individual Waste Water Treatment units in operation. J Excess treated water from individual treatment plant is sent to Central Effluent Treatment Plant (CETP). CETP is in operation with tertiary treatment. The Treated water from CETP is used in process. J Treated wastewater will be also used for plantation, dust suppression & other uses.
v.	The overall noise levels in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75 dBA (daytime) and 70 dBA (nighttime).	 J Low noise prone rotary equipment and vibration dampening has been one of the design aspects as a control measure for noise pollution. J Provision of acoustic hoods, silencers in steam ejectors as well as sound proof enclosures have also been made at various internal sites.

В.	General Conditions as per EC dated 7.11.2006	Status as on 31.03.2019					
vi.	The project proponent shall also comply with all the environmental protection measures and safeguards recommended in the EIA/EMP report. Further, the company must undertake socioeconomic development activities in the surrounding villages like community development programmes, educational programmes, drinking water supply and health care etc.	 J Environmental protection measures as proposed in the EIA and EMP report is being implemented. J Various socio-economic developmental activities in the area of Health, Women Empowerment, Education, Sports & culture, Infrastructure development etc. are on-going in 28 villages surrounding the project site. Recently, 5 medical mobile units have been added for immediate treatment to the local people. J Multi-specialty, 100 bedded hospitals (Medica TS) is now functioning very close to the plant site for facilitating health service to the community. 					
vii.	The project authorities shall utilize Rs. 1,525.00 Crores earmarked for the environmental pollution control measures judiciously to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.	Funds earmarked for the environmental pollution control measures are not diverted and is being utilized only for the said purpose.					
viii.	The Regional Office of this Ministry at Bhopal/CPCB/OPCB will monitor the stipulated conditions. A six monthly compliance report and	Six monthly compliance reports are being submitted regularly.					
	the monitored data along with statistical interpretation shall be submitted to them regularly.	Last Report Sent on 30.11.2018.					
ix.	The Project Proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the OPCB/Committee and may also be seen at Website of the Ministry of Environmental and Forests at http://envfor.nic.in. This shall be advertises within seven days from the date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same shall be forwarded to the Regional office.	Newspaper advertisement details: - Newspaper Language Date New Indian Express English 13.06.06 Sambad Odia 13.06.06					
Х	Project authorities should inform Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of commencing the land development work.	Complied.					

	Additional Conditions vide letter dated 10.10.2012	Status as on 31.03.2019
i)	The company shall install low NOx burners to mitigate NOx emissions from captive power plant.	There are three nos. of boilers of captive power plant. At each boiler, 8 Nos. of Low NOx burners have been installed to control NOx emissions.
ii)	Data on ambient air, stack and fugitive emission shall be regularly submitted online to Ministry's Regional Office at Bhubaneswar and Central Pollution Control Board as well as hard copy once in six months and display data on PM10, SO2 and NOx outside the premises at the appropriate place for the general public.	JSix Monthly compliance reports are sent in hard as well as soft copies to MoEF/OSPCB. The same is also available at company web site. JAAQ data is displayed at the entrance of the Plant (Plant's Main Gate) for information to general public through Electronic display board JFour nos. of CAAQMS (Two Nos. inside and Two Nos. outside plant premises) are in operation. JFor monitoring of stack emissions, Online Continuous emission monitoring systems have been installed at all the operating units' viz. Coke Oven battery#2, Battery #1, CPP1, SP, BF, SMS, LCP and HSM and all are in operation.
iii)	The National Ambient Air Quality Standard issued by the Ministry vide GSR No. 826(E) dated 16th November, 2009 shall be followed.	Air Quality standards conforming to NAAQS vide GSR 826 (E) has been referred for air quality monitoring and review.
iv)	The project proponent shall also submit six monthly reports on the status of the compliances of the stipulated environmental conditions including results of monitored data (both in hard copies as well as by e-mail) to the respective Regional Office of MoEF, the respective Zonal Office of CPCB and SPCB. The Regional Office of the Ministry at Bhubaneswar/CPCB/SPCB shall monitor the stipulated conditions.	JWe are submitting the six-monthly compliance report in stipulated time. JLast Six-monthly compliance reports for the period Apr'18 to Sep'18 was submitted to MoEF/ OSPCB Regional Office both in hard as well as soft copy on 30.11.18. J Soft copy of the half yearly progress report was also been sent to roez.bsr-mef@nic.in.
v)	The environmental statement for each financial year ending 31 march in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (protection Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliances of environmental conditions and shall also be sent to the respective Regional Offices of the MoEF by e-mail.	JEnvironment Statement for FY 2017 -18 was submitted to OSPCB on 27.09.2018 and the same for 2018-19 will be submitted before 30.09.2019. JBoth, Environment Statement and Status of Compliance of EC conditions have been uploaded on company's website. (www.tatasteel.com)
vi)	The company shall submit within three months their policy towards Corporate Environment Responsibility which should inter-alia address (i) Standard operating process/ procedure to being into focus any infringement/ deviation/ violation of the environmental or forests norms/ conditions, (ii) Hierarchical system or Administrative order of the Company to deal with environmental issues and	JCorporate Environmental Policy was submitted to MoEF; New Delhi vide our letter no. TSL/DEL/805/2013 dated 8.1.2013. JCopy of the same was also submitted to MoEF, Bhubaneswar Office.

Additional Conditions vide letter dated Status as on 31.03.2019 10.10.2012
ensuring compliances to the environmental
clearances conditions and (iii) system of reporting
of noncompliance/ violation of environmental
norms to the Board of Directors of the Company
and/or shareholders.

	Additional Safeguards vide letter dated 13.5.2015	Compliance status as on 31.03.2019
2i	Project proponent should install 24x7 air and water monitoring devices to monitor the air emission and effluent discharge, as provided by Central Pollution Control Board (CPCB) and submit the report to Ministry and its Regional office	JTo monitor the ambient air quality, 4 nos. of continuous ambient air quality monitoring station (CAAQMS) have been installed and are in operation. J Continuous emission monitoring system (CEMS) have been installed at all the major stacks like Coke Battery No. 1 & 2, Captive power plant, Sinter Plant, Blast Furnace, Steel Melting Shop, Lime Calcination Plant and Hot Strip Mill. J Online Water quality monitoring stations installed at the outlet of BOD plant of Coke Oven Unit.
2ii	For Wet quenching: permission to start the coke ovens with wet quenching till CDQ is stabilized by June 2016, thereafter maintain wet quenching as a standby and use for 20 days (3 weeks) in a year or per annum for maintenance or operation exigencies	JCDQ unit for Battery No. 1 & 2 is in operation. JWet quenching system is maintained as standby
2iii	For LDO: Use of LDO for generation of power in power plants and DG set till Blast Furnace gas is available for power generation in power plants and there after maintain LDO as "Standby" and use for 15 days(two weeks) per annum for maintenance or operational exigencies.	BF Gas generated is used for power generation in Captive Power Plant. LDO is being maintained as standby fuel. DG sets are operated only in case of exigencies.
	Additional Conditions vide letter dated 20.12.2016	Compliance status as on 31.03.2019
7.i	For Wet quenching: permission to start the coke ovens with wet quenching till the CDQ is stabilized by November 2016, thereafter maintain wet quenching as a standby and use for 20 days (3 weeks) in a year or per annum for maintenance or operational exigencies.	JCDQ unit for Battery No. 1 & 2 is in operation. Wet quenching system is maintained as standby

AMBIENT AIR QUALITY (INSIDE PLANT)

Period: Oct'18 to March'19

SI. No	Samplin g Stations	Month	PM ₁₀ µg /m³	PM _{2.5} μg /m ³	SO ₂ μg / m ³	NO _x μg / m³	CO mg/m³	Ozone (Ο ₃) μg/m³	Lead (Pb) µg/m³	Ammonia (NH₃) μg/m³	Benze ne (C ₆ H ₆)	Benzo (a) Pyrene ng /m³	Arsenic (As) ng /m³	Nickel (Ni) ng/m³
1	Coke Oven		73.5	34.8	16.2	18.4	0.40	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
2	Power Plant	-	69.7	33.6	10.4	11.6	0.34	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
3	Gate-1	0.1140.	75.1	36.5	13.3	15.3	0.22	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
4	HSM	Oct'18 to March'19	74.5	35.5	10.0	11.7	0.27	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
5	Gate No:4		73.4	34.4	14.7	16.1	0.34	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
6	SMS		73.9	35.6	11.2	12.4	0.28	<10	<0.01	<20	< 2.0	BDL	< 2.0	< 2.0
	C.P.C.B Sta	andard	100 (24 Hrs.)	60 (24 Hrs.)	80 (24 Hrs.)	80 (24 Hrs.)	2 (8 Hrs.)	100 (8 Hrs.)	1 (24 Hrs.)	400 (24 Hrs.)	05 (Annua I)	01 (Annual)	06 (Annual)	20 (Annu al)

Noise Monitoring Report

Period: Oct'18 to March'19

			t'18	No	v'18	Dec	c'18	Jar	n'19	Feb	o'19	Marc	ch'19		Ave	rage	
SI N o	NOISE MONITORI NG LOCATION S	in dB A (Da y Tim e)	in dBA (Nig ht Tim e)	in dBA (Da y Tim e)	NOISE STANDAR DS Day time (in dBA)	in dBA (Nig ht Tim e)	NOISE STANDAR DS Night time (in dBA)										
1	Sinter Plant	60. 2	52.6	61.3	50.6	61.2	51.4	61.7	53.9	61.1	50.8	64.3	53	61.6	75	52.1	70
2	Blast Furnace	68. 7	48.9	61.4	48.7	58.8	50.1	60.9	49.7	61.2	49.3	59.4	48.8	61.7	75	49.3	70
3	SMS	57. 8	43.4	55.6	43.7	55.1	51.1	61.6	45.9	62	49.3	51.1	48.7	57.2	75	47.0	70
4	Gate-1	62. 7	50.2	57.2	48.8	61.1	50.2	67.7	48.8	63.1	51.4	61.4	51.4	62.2	75	50.1	70
5	RMHS	62. 2	49.4	62.1	47.8	64.2	51.7	66.8	44.8	63.2	48.8	60.5	49.3	63.2	75	48.6	70
6	HSM	61. 7	48.4	56.1	47.4	58.9	52.4	61.7	44.1	62.7	48.9	52.3	48.8	58.9	75	48.3	70
7	LCP	61. 3	46.1	54.7	44.1	59.9	49.8	61.4	49.2	59.6	48.3	60.7	47.6	59.6	75	47.5	70

[#] Day time: 06.00am to 10.00pm; Night time: 10.00pm to 06.00am

	GROUND WATER QUALITY										
			Per	iod: Oct'18	to March'	19					
SI. No.	Parameter	Standard as per BIS: 10500	Oct'18	Nov'18	Dec'18	Jan'18	Feb'18	March'18	Average		
1	pH Value	6.5-8.5	6.46	6.31	6.89	6.67	7.14	7.21	6.8		
2	Colour	5	CL	CL	CL	CL	CL	CL	CL		
3	Odour	U/O	U/O	U/O	U/O	U/O	U/O	U/O	U/O		
4	Taste	Agreeable	AL	AL	AL	AL	AL	AL	AL		
5	Turbidity (NTU), max	5	0.41	0.33	0.41	0.68	0.63	0.21	0.45		
6	Anaionic Detergents, mg/l, max	0.2	ND	ND	ND	ND	ND	ND	ND		
7	Aluminium as Al, mg/l, max	0.03	BDL	BDL	BDL	BDL	BDL	BDL	BDL		
8	Alkalinity , mg/l, max	200	77	83	71	56	48	76	68.5		
9	Total Hardness (as CaCO3), mg/l, max	300	89.3	132	112	144	103	88.3	111.4		
10	Electrical Conductivity at 250C, µmho/cm	\$	189	247	188	172	214	189	199.8		
11	Calcium (as Ca), mg/l, max	75	18	37	28	41	23	21	28.0		
12	Magnesium as Mg, mg/l, max	\$	4.2	1.6	3.1	4.1	8.4	6.4	4.6		
13	Sodium as Na, mg/l, max	\$	10.1	5.7	4.3	5.1	3.9	4.6	5.6		
14	Potassium as K, mg/l, max	\$	0.46	0.22	0.18	0.11	0.08	0.33	0.2		
15	Copper (as Cu), mg/l, max	0.05	BDL	BDL	BDL	BDL	BDL	BDL	BDL		
16	Iron (as Fe), mg/l, max	0.3	0.14	0.22	0.16	0.36	0.37	0.25	0.28		

17	Manganese (as Mn), mg/l, max	0.1	BDL						
18	Chloride (as Cl), mg/l, max	250	30.4	27.3	18.3	21.4	16.8	17.3	21.92
19	Sulphate (as SO4), mg/l, max	200	28.3	17.4	28.1	24.3	24.1	17.8	23.33
20	Nitrate (as NO3), mg/l, max	45	0.18	0.16	0.24	0.36	0.32	0.38	0.27
21	Fluoride (as F), mg/l, max	1	0.08	0.07	0.1	BDL	0.12	0.07	0.09
22	Phenolic Compounds (as C6H5OH), mg/l, max	0.001	BDL						
23	Mercury (as Hg), mg/l, max	0.001	BDL						
24	Cadmium (as Cd), mg/l, max	0.01	BDL						
25	Selenium (as Se), mg/l, max	0.01	BDL						
26	Arsenic (as As), mg/l, max	0.05	BDL						
27	Cyanide (as CN), mg/l, max	0.05	BDL						
28	Lead (as Pb), mg/l, max	0.05	BDL						
29	Zinc (as Zn), mg/l, max	5	0.41	0.21	0.46	0.32	0.26	0.11	0.30
30	Nickel as Ni, mg/l, max	\$	BDL						

	Total		0.04	0.09	0.18	BDL	0.13	0.16	0.12
31	Chromium	\$							
	as Cr, mg/l,								
	max								
32	Chromium		0.004	0.006	0.009	0.004	0.005	0.007	0.01
	(as Cr+6),	0.05							
	mg/l, max								
33	Mineral Oil,	0.01	ND	ND	ND	ND	ND	ND	ND
	mg/l, max	0.01							
34	Total		ND	ND	ND	ND	ND	ND	ND
	Coliform,	\$							
	MPN/ 100								
	ml								
35	E-coli ,	_	ND	ND	ND	ND	ND	ND	ND
	MPN/ 100	\$							
	ml								
	Total		182	151	161	189	185	173	174
36	Dissolved	500							
	Solids, mg/l,								
	max								
	Residual,		ND	ND	ND	ND	ND	ND	ND
37	free	0.2							
	Chlorine,	0.2							
	mg/l, min								
38	Boron mg/l	1	BDL	BDL	BDL	BDL	BDL	BDL	BDL
	, max								

VOC Monitoring Report of Coke Oven

(Monthly average from Oct'18 to March'19)

SI. No	Monitoring Location	month	Benzene (C ₆ H ₆) μg/m³	Benzo (a) Pyrene ng /m³
1	Coke Oven Plant		1.14	0.11
2	Near Coke Oven Battery#1		<2.0	BDL
3	Near Coke Oven Battery#2	Oct'17 to March'18	<2.0	0.13
4	Near CDQ Area		1.06	BDL
	C.P.C.B Stan	dard	05 μg/m³ (Annual)	01 ng/m³ (Annual)

---X--



New Office building – Tata Steel Kalinganagar (TSK)



Second Fire Station at TSK



Plantation inside Plant premises



Garden development & Landscaping



---X---



Water sprinkler at raw material yard